МИНИСТЕРСТВО НА ФИНАНСИТЕ
АГЕНЦИЯ "МИТНИЦИ"
ЦЕНТРАЛНО МИТНИЧЕСКО УПРАВЛЕНИЕ

ИСКАНИЯ ЗА СУСПЕНДИРАНЕ НА МИТАТА ОТ 1 ЯНУАРИ 2025 г., ПОСТЪПИЛИ В ГЕНЕРАЛНА ДИРЕКЦИЯ "ДАНЪЧНО ОБЛАГАНЕ И МИТНИЧЕСКИ СЪЮЗ" НА ЕВРОПЕЙСКАТА КОМИСИЯ

1. Настоящият документ представя исканията за въвеждане на автономни мерки за суспендиране на митата на определени химически и индустриални стоки, постъпили в определения срок (15 март 2024 г.) в ГД "Данъчно облагане и митнически съюз" на Европейската комисия. Исканията се разглеждат в Работна група "Икономически тарифни въпроси" на ЕК и се предлагат за одобрение от Съвета на Европейския съюз. Мерките, които касаят, са за пълно или частично суспендиране на митата от 1 януари 2025 г.
2. Тарифните кодове и текстовите описания на стоките могат да претърпят допълнително уточняване. В настоящия документ са описани всички оригинални искания на държавите членки, както и на Република Турция в рамките на митническия съюз ЕС– Турция.
3. Исканията са подредени по възходящ ред съгласно Комбинираната номенклатура на ЕС.
4. Формулярът за възражение срещу искане от този списък се намира на адрес https://customs.bg/wps/portal/agency/home/info-business/customs-activities/suspending.
5. Български производители, които считат, че тези предложения накърняват икономическите им интереси могат да подадат възражения, като използват формуляр, чийто образец се намира на адрес https://customs.bg/wps/portal/agency/home/info-business/customs-activities/suspending. Срокът за подаване на възражения по нови искания е до 14.06.2024 г. (в Агенция"Митници" – 1.06.2024 г.), а по исканията за продължаване на мерките за суспендирания - до 10.05.2024 г.
6. Коментари по исканията могат да бъдат направени до 14.06.2024 г. за нови искания (в Агенция"Митници" – 1.06.2024 г.) и до 10.05.2024 г. за искания за продължаване на мерките. За целта се използва формулярът за подаване на възражения.

Възраженията и коментарите по исканията за суспендиране на митата, придружени с необходимите мотивационни документи се подават по факс: 02 / 9859 4066.

За допълнителна информация относно суспендирането на митата:
дирекция "Митническа дейност и методология"
02 / 9859 4452 – Бояна Господинова

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
2906 19 00	(1*S*,2*S*,3*R*,5*S*)-(+)-2,3-pinanediol (CAS RN 18680-27-8) with a purity by weight of 98 % or more	АВСТРИЯ	1990365	ново
2914 29 00	3-Methylcyclopent-2-enone (CAS RN 2758-18-1) with a purity by weight of 98 % or more	ИТАЛИЯ	1413088	ново
2917 19 80	20-[(2-Methylpropan-2-yl)oxy]-20-oxoicosanoic acid (CAS RN 683239-16-9) with a purity by weight of 98 % or more	ДАНИЯ	2003292	ново
2920 90 70	Triisopropyl borate (CAS RN 5419-55-6) with a purity by weight of 99 % or more	ФРАНЦИЯ	1906519	ново
2922 19 00	(1*R*,3*S*)-3-aminocyclopentan-1-ol benzoate (CAS RN 1846582-38-4) with a purity by weight of 95 % or more	ИСПАНИЯ	1816713	ново
2922 49 85	Glycine hydrochloride (CAS RN 6000-43-7): - in the form of a white crystalline powder, - with a purity by weight of 95 % or more, - with a chloride-content by weight of 25,0 % or more but not more than 35 %, - with a pH value of 0,75 or more, but not more than 2,5, - with a humidity content by weight of 1 % or less, whether or not with addition of silicon-dioxide	УНГАРИЯ	1994384	ново
2923 90 00	*Bis*(*N*,*N*,*N*-trimethyladamantan-1-aminium) sulfat (CAS RN 1000777-61-6) with a purity by weight of 95 or more, also as aqueous solution	ГЕРМАНИЯ	1853158	ново
2924 19 00	Carbamic acid, *N*-methyl-N-(2-oxopropyl)-, 1, 1-dimethylethyl ester (CAS RN 532410-39-2) with a purity by weight of 90 % or more	ФРАНЦИЯ	1650443	ново
2924 29 70	(2*S*)-6-amino-2-({[(9*H*-fluoren-9-yl)methoxy]carbonyl}amino)hexanoic acid hydrochloride (CAS RN 139262-23-0) with a purity by weight of 90 % or more	ИТАЛИЯ	1442594	ново
2924 29 70	*N*-[(9*H*-fluoren-9-ylmethoxy)carbonyl]glycine (CAS RN 29022-11-5) with a purity by weight of 99 % or more	ИТАЛИЯ	1436353	ново
2924 29 70	*N*-Benzyloxycarbonylglycine (CAS RN 1138-80-3), with a purity by weight of 99 % or more	ИТАЛИЯ	1442672	ново
2924 29 70	2-(Dimethylaminomethylidene)-4-methoxy-3-oxo-*N*-[(2,4,6-trifluorophenyl)methyl]butanamide (CAS RN 1846582-17-9) with a purity by weight of 95 % or more	ИСПАНИЯ	1816815	ново
2925 19 95	2-{2-[2-(1,3-Dioxo-2,3-dihydro-1*H*-isoindol-2-yl)ethoxy]ethoxy}acetic acid (CAS RN 75001-09-1), with a purity by weight of 95 % or more	ИТАЛИЯ	1607835	ново
2925 29 00	N,N-Dibutyl[bis(diethylamino)]methaniminium chloride (CAS RN 89450-30-6) with a concentration of more than 30 but not more than 36 percent by weight and	БЕЛГИЯ	1966069	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	sodium chloride (CAS RN 7647-14-5) with a concentration not more than 14 percent by weigh			
2928 00 90	Daminozide (ISO) (CAS RN 1596-84-5) with a purity by weight of 97 % or more	НИДЕРЛАНДИЯ	1999197	ново
2930 90 98	Propane-1,3-dithiol (CAS RN 109-80-8) with a purity by weight of 98 % or more	ИТАЛИЯ	1398021	ново
2933 39 99	2,5-Dichloro-4,6-dimethylpyridine-3-carbonitrile (CAS RN 91591-63-8) with a purity by weight of 99 % or more	АВСТРИЯ	2004633	ново
2933 39 99	2-Amino-3-bromo-5-nitropyridine (CAS RN 15862-31-4) with a purity by weight of 98 % or more	ИСПАНИЯ	1816887	ново
2933 39 99	2,4-Dichloropyridine-3-carboxaldehyde (CAS RN 134031-24-6) with a purity by weight of 97 % or more	ИТАЛИЯ	1445998	ново
2933 39 99	*N*-[(1*S*,5*R*)-8-benzyl-8-azabicyclo[3.2.1]octane-3-yl]-2- methylpropanamide (CAS RN 376348-67-3) with a purity by weight of 98 % or more	ИТАЛИЯ	1776167	ново
2933 39 99	Fluroypyr-meptyl(ester) (CAS RN 81406-37-3) with a purity by weight of 95 % or more	БЕЛГИЯ	1821944	ново
2933 39 99	Cyantraniliprole (CAS RN 736994-63-1) with a purity 90 % by weight or more	ГЕРМАНИЯ	1895794	ново
2933 59 95	Thiopental (INN) (CAS RN 76-75-5) of a purity by weight of 98,5 % or more	ГЕРМАНИЯ	1998126	ново
2933 59 95	4-Methyl-7*H*-pyrrolo[2,3-d]pyrimidine (CAS RN 945950-37-8) with a purity by weight of 98 % or more	СЛОВЕНИЯ	1897224	ново
2933 59 95	Piperazin-2-one (CAS RN 5625-67-2) with a purity by weight of 96 % or more	ИТАЛИЯ	1451763	ново
2933 69 80	4-(4,6-*Bis*((biphenyl-4-yl)-1,3,5-triazine-2-yl)-1,3-benzodiole (CAS RN 182918-16-76) with a purity by weight of 96 % or more	ГЕРМАНИЯ	1904372	ново
2933 99 80	(1*R*,5R)-Ethyl 3-benzyl-3-azabicyclo[3.1.0]hexane-1-carboxylate hydrochloride (CAS RN 2914217-81-3) with a purity by weight of 97 % or more	ИТАЛИЯ	1561931	ново
2933 99 80	(*S*)-2-Methylpyrrolidine-2-carboxylic acid hydrochloride (CAS RN 1508261-86-6) with a purity by weight of 98 % or more	ИТАЛИЯ	1607739	ново
2933 99 80	*tert*-Butyl (2*S*)-2-carbamoylpyrrolidine-1-carboxylate (CAS RN 35150-07-3) with a purity by weight of 97 % or more	ИТАЛИЯ	1867643	ново
2933 99 80	*tert*-Butyl (3*R*)-3-aminopyrrolidine-1-carboxylate (CAS RN 147081-49-0) with a purity by weight of 97 % or more	АВСТРИЯ	1990427	ново
2934 20 80	3-Methyl-1,2-benzothiazole-1,1-dioxide (CAS RN 34989-82-7) with purity by weight of 95 % or more	ГЕРМАНИЯ	1851279	ново
2934 99 90	Thenoic acid (CAS RN 1918-77-0) with a purity by weight of 97 % or more	АВСТРИЯ	1990498	ново
2934 99 90	(4R,6S)-6-Methyl-7,7-dioxo-5,6-dihydro-4H-thieno[2,3-b]thiopyran-4-ol (CAS RN 147128-77-6) with a purity by weight of 94 % or more	ИСПАНИЯ	1965658	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
2935 90 90	*N*',*N*'''-[(2*S*,3E,5*S*)-1,6-diphenylhex-3-ene-2,5-diyl]*bis*(*N*,*N*-dimethylsulfuric diamide) (CAS RN 1247119-27-2), with a purity by weight of 70 % or more	ИТАЛИЯ	1451870	ново
2935 90 90	4-Chloro-3-nitro-5-sulphamoylbenzoic acid (CAS RN 22892-96-2) with a purity by weight of 96 % or more	ИТАЛИЯ	1397842	ново
3206 19 00	Nickel antimony titanium yellow rutile (C.I. pigment yellow 53) (CAS RN 8007-18-9)	БЕЛГИЯ	2257040	ново
3206 19 00	Chrome antimony titanium buff rutile (C.I. pigment brown 24)	БЕЛГИЯ	2254709	ново
3206 20 00	cobalt chromite blue green spinel (C.I. pigment blue 36)	БЕЛГИЯ	2254788	ново
3206 20 00	Copper chromite black spinel (C.I. pigment black 28)	БЕЛГИЯ	2256979	ново
3206 20 00	Cobalt chromite green spinel (C.I. pigment green 26)	БЕЛГИЯ	2254854	ново
3206 20 00	Nickel iron chromite black spinel (C.I. pigment black 30) (CAS RN 71631-15-7)	БЕЛГИЯ	2257118	ново
3206 20 00	Chromium iron oxide (C.I. pigment brown 29)	БЕЛГИЯ	2254745	ново
3206 49 70	Cobalt titanate green spinel (C.I. pigment green 50) (CAS RN: 68186-85-6)	БЕЛГИЯ	2254986	ново
3206 49 70	Cobalt aluminate blue spinel (C.I. pigment blue 28)	БЕЛГИЯ	2254954	ново
3402 42 00	Copolymer of non-hydrolysable polysiloxane and polyether containing by weight 90 % of octamethylcyclotetrasiloxane (CAS: 556-67-2) and 10 % of decamethylcyclopentasiloxane (CAS 540-97-6) with a viscosity index of 800 or more but not more than 1400	ТУРЦИЯ	2231038	ново
3402 42 00	Copolymer of non-hydrolysable polysiloxane and polyether containing by weight 90 % of octamethylcyclotetrasiloxane (CAS: 556-67-2) and 10 % of decamethylcyclopentasiloxane (CAS 540-97-6) with a viscosity index of 300 or more but not more than 450	ТУРЦИЯ	2230983	ново
3402 42 00	Copolymer of non-hydrolysable polysiloxane and polyether containing by weight 90 % of octamethylcyclotetrasiloxane (CAS: 556-67-2) and 10 % of decamethylcyclopentasiloxane (CAS 540-97-6) with a viscosity index of 700 or more but not more than 1100.	ТУРЦИЯ	2231001	ново
3402 42 00	Polysiloxane and polyether copolymer containing by weight; - 60 % or more but not more than 90 % of polyalkylene oxide methylsiloxane copolymer (Cas No: 68937-55-3) and - 10 % or more but not more than 40 % of polyalkylene glycol (Cas no: 9041-33-2) with a viscosity index of 100 or more but not more than 1000.	ГЕРМАНИЯ	2230899	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
3808 93 90	Preparation in the form of powder, containing by weight 90 % or more of a mixture of Gibberellins A4 and A7 (CAS RN 8030-53-3)	НИДЕРЛАНДИЯ	2001114	ново
3815 19 90	Catalyst - consisting of aluminum phosphate supported on aluminum oxide and silicon and a mixture of molybdenum, nickel and metal oxides, - in the form of solid spheres, - of a diameter of 1,3 mm or more but not more than 19 mm, - used for protecting against organic and inorganic impurities by treating with hydrogen in diesel	ТУРЦИЯ	2078073	ново
3815 19 90	Catalyst - consisting of a mixture of aluminum phosphate supported on aluminum oxide and silicon, molybdenum, nickel and oxides, - in the form of solid spheres, - of a diameter of 1,3 mm or more but not more than 19 mm, - used for protecting against organic and inorganic impurities and - removing sulfur and nitrogen by treating with hydrogen in kerosene, for use in the production of kerosene with JET A1 specification which is utilized in kerosene hydrotreater units by treating kerosene streams in refineries	ТУРЦИЯ	2078278	ново
3824 99 92	Mixture, containing: - 90 % or more but not more than 95 % by weight of poly(oxy-1,2-ethanediyl),α-(methylphenyl)-ω-hydroxy- (CAS RN 37281-57-5), and - 5 % or more but not more than 10 % by weight of poly(oxy-1,2-ethanediyle),α-(dimethylphenyl)-ω-idroxy (CAS RN 61723-82-8)	ИТАЛИЯ	1708409	ново
3824 99 93	Reaction mass of phosphate esters: Mixture of dihexadecyl hydrogen phosphate and hexadecyl dihydrogen phosphate	ГЕРМАНИЯ	1853093	ново
3901 30 00	Terpolymer of ethylene, vinyl acetate and methacrylic acid	ГЕРМАНИЯ	2040183	ново
3901 30 00	Copolymer of ethylene and vinyl acetate with - a vinyl acetate content of 28 % or more but not more than 49,5 % by weight, and - a melt flow rate of less than 5g/10 min (MFR 190 °C/2.16 kg, ASTM D1238) in the form of pellets	ГЕРМАНИЯ	2221371	ново
3901 90 80	Terpolymer of ethylene, isobutyl acrylate and methacrylic acid, in the form of pellets	ГЕРМАНИЯ	2070852	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
3901 90 80	Terpolymer of ethylene, butyl acrylate and carbon monoxide in the form of pellets	ГЕРМАНИЯ	2064110	ново
3907 29 20	Glycerol propylene glycol ether based polyol with a hydroxyl number of 541 or more but not more than 587	ТУРЦИЯ	2071861	ново
3907 29 20	Polyether polyol with a total bio content of 30 % and containing by weight; - 9 % or more but not more than 15 % of palm oil, - 20 % or more but not more than 25 % of sucrose and sorbitol with a hydroxyl number of 410 or more but not more than 460 and a viscosity index of 2700 or more but not more than 7000	ТУРЦИЯ	2071921	ново
4408 39 95	Igaganga sheets for veneering: - with a largest dimension of 900 mm or more, but not more than 3 250 mm, - with a smallest dimension of 95 mm or more but not more than 2 000 mm, - with a thickness of more than 1 mm, but not more than 4 mm, unsanded and not planed	ФРАНЦИЯ	1969015	ново
4408 39 95	Iroko sheets for veneering: - with a largest dimension of 900 mm or more, but not more than 3 250 mm, - with a smallest dimension of 95 mm or more but not more than 2 000 mm, - with a thickness of more than 1 mm, but not more than 4 mm, unsanded and not planed	ФРАНЦИЯ	1807658	ново
4408 39 95	Igaganga sheets for veneering: - with a largest dimension of 900 mm or more, but not more than 3 250 mm, - with a smallest dimension of 95 mm or more but not more than 2 000 mm, - with a thickness of more than 1 mm, but not more than 4 mm, unsanded and not planed	ФРАНЦИЯ	1969015	ново
4408 39 95	Ozigo sheets for veneering: - with a largest dimension of 900 mm or more, but not more than 3 250 mm, - with a smallest dimension of 95 mm or more but not more than 2 000 mm, - with a thickness of more than 1 mm, but not more than 4 mm, unsanded and not planed	ФРАНЦИЯ	1807734	ново
6001 10 00 6001 92 00	Faux rabbit fur knitted fabric with a shiny texture, with a pile height of 1 mm or more but not more than 50 mm, for use in plush toy production (1)	ТУРЦИЯ	2133004	ново
8407 33 80	Twin cylinder, four stroke internal combustion spark-ignition engine with a cylinder capacity not exceeding 1000 cm3,	ПОЛША	2141022	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	with overall dimensions of not more than: 450 mm (length) x 470 mm (width) x 600 mm (height), - a power of 40 kW or more but not more than 86 kW, - whether or not equipped with single overhead cam and starter, spark plug wires, fuel rail, and injectors [for use in the manufacture of all-terrain or utility task vehicles] (1)			
8407 33 80	Single cylinder, four stroke internal combustion spark-ignition engine with a cylinder capacity not exceeding 570 cm3, - with overall dimensions of not more than: 390 mm (length) x 490 mm (width) x 590 mm (height), - a power of 22 kW or more but not more than 35 kW, - equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (+/- 1 degree), - whether or not equipped with starter, throttle body, spark plug wire, fuel rail and injector [for use in the manufacture of all-terrain or utility task vehicles] (1)	ПОЛША	2140978	ново
8407 34 91	Dual cylinder, four stroke internal combustion spark-ignition engine with a cylinder capacity of 1000 cm3 or more but not more than 1250 cm3, - with overall dimensions of not more than: 700 mm (length) x 430 mm (width) x 610 mm (height), - a power of 60 kW or more but not more than 110 kW, - whether or not equipped with a starter, outfitted with a throttle body, two or more fuel injectors, a stator [for use in the manufacture of motorcycle bikes] (1)	ПОЛША	2140866	ново
8407 34 99	Dual cylinder, air cooled, four stroke 49 degree V-twin internal combustion spark-ignition engine with a cylinder capacity exceeding 1800 cm3: - with overall dimensions of not more than: 800 mm (length) x 500 mm (width) x 600 mm (height), - a power of 60 kW or more but not more than 75 kW, - equipped with a semi-dry oil sump, - whether or not equipped with a starter, outfitted with a throttle body, two or more fuel injectors, a stator [for use in the manufacture of motorcycle bikes] (1)	ПОЛША	2140932	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
8409 99 00	Die cast aluminum housing for electronic throttle control or exhaust gas recirculation systems: - high pressure-casted of EN AC-46000 aluminum, - shot-blasted and machined, - of air tightness of 2 g/h at 20 °C under 2,5 bar relative pressure, - with a height of 100 mm or more , but not more than 135 mm, - with a width of 115 mm or more, but not more than 150 mm, with a weight of 210 g or more, but not more than 465 g	ПОЛША	2556095	ново
8419 50 80	Aluminum heat exchanger for gas boilers designed for highly efficient heat transfer: - with a height of 100 mm or more, but no more than 120 mm, - with a length of 235 mm, but no more than 280 mm, - with 250 mm or more in width, but no more than 280 mm, - for a power output of 25 kW but no more than 35 kW, a weight of 8 kg or more, but no more than 10 kg	СЛОВАКИЯ	2132672	ново
8479 89 97	Integrated automated turnkey machinery line for the complete manufacturing of sodium-ion batteries, from slurry mixing through to battery packaging, including, in particular, machines for coating and calendering of strips, cell assembly and their electrical formation	ФРАНЦИЯ	2133182	ново
8481 80 99	Solenoid valve of continuous variable valve timing system of combustion engine for oil flow control according to engine speed and load: - in metal cover, - with electrical connector, - with a force of not more than 10 N, - with an operating voltage of 9 VDC or more but not more than 16 VDC - with a length of 80 mm but not more than 110 mm, - with a width of 80 mm but not more than 110 mm, - with a height of 20 mm but not more than 30 mm for use in the manufacture of engines of motor vehicles(1)	СЛОВАКИЯ	2140412	ново
8483 10 95	Stepped shaft made of carbon steel with: - rolled, involute profiled, splined shaft end, the helix angle of which is at least 0°15,5’ but not more than 0° 21,5’ - a largest diameter of 16 mm or more but not more than 18 mm	УНГАРИЯ	2132579	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- a length of 137 mm or more, but not more than 155 mm a weight of 0,12 kg or more but not more than 0,28 kg			
8483 90 89	Hub gear made of cold rolled carbon steel (per ASTM A1008), molded into the plastic and pressed on pinion, with: - an outer diameter of 81,2 mm or more, but not more than 82,55 mm, - an inner diameter of 25,9 mm or more, but not more than 25,97 mm, - a height of the lower side of inner diameter of 11,63 mm or more, but not more than 12,13 mm, - a height of the upper side of inner diameter of 3,25 mm or more, but not more than 3,5 mm, - an overall height of 11,63 mm or more, but not more than 19,5 mm for use in the manufacture of vehicle's steering system	ПОЛША	2545142	ново
8503 00 99	Pressure casted stator housing of an electric motor: - of EN AC-46000 aluminum, - shot-blasted and machined, - leakproof to the degree of 2 g per hour or less under 2,5 bar pressure, - with an HBW of 60 or more (2,5/62,5, according to ISO 6506), - with a tensile strength of 240 N/mm2 or more, - with a height of 70 mm or more, but not more than 76 mm, - with a width of 155 mm, but not more than 162 mm, with a weight of 330 g or more but not more than 360 g	ПОЛША	2555880	ново
8503 00 99	Pressure casted rotor front plate or cover of an electric supercharger: - of EN AC-46000 aluminum, - shot-blasted and machined, - leakproof to the degree of 2 g per hour or less under 2,5 bar pressure, - with an HBW of 60 or more (2,5/62,5, according to ISO 6506), - with a tensile strength of 240 N/mm2 or more, - with a height of 22 mm or more , but not more than 26 mm, - with a diameter of 128 mm or more, but not more than 136 mm, - with a weight of 220 g or more, but not more than 250 g	ПОЛША	2556164	ново
8505 11 10	Magnetized upper rotor made with steel stack according to standards ASTM A677-07 grade 47F180 or JIS C 2552 Grade 50A310, with:	ПОЛША	2544759	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- twelve permanent magnets made with neodymium-iron-boron (per MMPA 0100), enclosed in stamped steel stack ring, - a residual induction value 1.21 T or more, but not more than 1.32 T, measured in 25 Degree Celsius, - an inner diameter of 22,735 mm or more, but no more than 22,835 mm, - an outer diameter of 30,725 mm or more, but no more than 38,025 mm, for use in the manufacture of vehicle's steering system			
8536 41 90	Power relay with the function of safely connecting or disconnecting the charging and/or power circuit of 48V batteries in a plastic case, containing: - current sensor 50A/400V - high voltage MILD fuse 70V/300A, - whether or not cable with connector, for use in the production of rechargeable batteries for hybrid and electric vehicles (1)	СЛОВАКИЯ	1398260	ново
8538 90 99	LTE antenna for vehicle emergency call system: - with an operating direct current voltage of 4 V or more but not more than 16 V, - in a plastic housing, - with mounting brackets - whether or not with a cable with a connector, for use in the manufacture of motor vehicles (1)	СЛОВАКИЯ	2176104	ново
8708 80 99	Ball plastic bearing of the upper mounting of the damper of motor vehicles of circular shape, with: - with an external diameter of 120 mm or more, but not more than 160 mm and - with an internal diameter of 70 mm or more, but not more than 100 mm for use in the manufacture of goods of Chapter 87 (1)	СЛОВАКИЯ	1398175	ново
8708 94 99	Assist Housing made of aluminum alloy (per DIN EN 1706 GRADE AC-46000) with surface treatment of aluminum oxide coating (per ASTM B580 type E) with: - a length of 181,04 mm or more, but not more than 183,04 mm, - a width of 130,32 mm or more, but not more than 132,32 mm, - a height in worm shaft axis of 145,71 mm or more, but not more than 146,11 mm, - a dust cover of 40,3 mm or more, but not more than 43,339 mm,	ПОЛША	2544894	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- a pinion hole dimension of 35,80 mm or more, but not more than 35,90 mm, - a rack housing connection with a mounting pads screw hole dimension 9,25 mm or more, but not more than 9,75 mm, - a power pack connection with a screw mounting pad dimension of 6,85 mm or more, but not more than 7,15 mm, - a gear bore diameter of 107,5 mm or more, but no more than 108,5 mm, for use in the manufacture of vehicle's steering system			
8708 94 99	Lower Shaft made of aluminum alloy (per ASTM B221M grade 6105), air quenched and tempered with: - a ultimate torsional strength value of 260 Nm or more, - a length of 296,7 mm or more, but not more than 297,8 mm, - an external 18-tooth spline on all shaft length with major diameter of 28,7 mm or more, but not more than 29 mm, to connect with mating tubular steering shaft, - an inner hole with diameter 19,42 or more, but not more than 19,72 mm, - an 18-tooth internal spline with a minor diameter of 19,7 mm or more, but not more than 20 mm for connecting with mating Shaft Lower Stub for use in the manufacture of vehicle's steering system	ПОЛША	2551124	ново
8708 94 99	Tubular Steering Shaft made of carbon steel welded tube (per EN 10305/2, E235 + C or GB/T699 grade 20) with: - an ultimate torsional strength load of 300 Nm or more and J.A.E.L values of 275 Nm or more, - a length of 245,48 mm or more, but not more than 287,5 mm, - an outer diameter of 23,95 mm or more, but not more than 32,25 mm, - an interface for steering wheel connection either in a form of an external 40-tooth spline with major diameter of 17,1 mm or more, but not more than 17,5 mm and an internal thread M12x1.75-6H or in a form of an external hexagon with a short diagonal of 15,05 mm or more, but not more than 15,35 mm and an internal thread M10x1.5-6H, - an interface for Shaft Tubular Female Steering either in a form of an internal 10-tooth spline of length of 98 mm or more, but not more than 160 mm, with minor diameter of 16,1 mm or more, but not more than 16,4 or in a form of an	ПОЛША	2551185	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	internal 48-tooth spline of length of 151 mm or more, but not more than 160 mm, with minor diameter of 23,2 mm or more, but not more than 23,3 mm, - with or without an outer tubular side with two slots for use in the manufacture of vehicle's steering system			
8708 94 99	Bar Torsion made of carbon alloy steel (per SAE J1268, grade 5160H of modified chemistry for carbon content of 0.53 or more, but not more than 0.56) with: - a shaft torsional stiffness of 2,5 Nm/degree or more, but not more than 2,7 Nm/degree, - a length of 107,75 mm or more, but no more than 108,25 mm, - an outer diameter of 6,38 mm or more, but no more than 6,42 mm, - two external 18-tooth splines on both shaft ends with a major diameter of 6,7 mm or more, but no more than 6,85 mm, as interface to pressing with matting input and output shafts, - entire surface shot peened for use in the manufacture of vehicle's steering system	ПОЛША	2555819	ново
8708 94 99	Upper Assist Shaft made of carbon steel (per GB/T699 grade 45) with: - an ultimate torsional strength load of 325 Nm or more and J.A.E.L values of 275 Nm or more, - a length of 165,3 mm or more, but not more than 204,2 mm, - an outer diameter of 22,87 mm or more, but not more than 22,92 mm, - an internal hole of diameter 6,5 or more, but not more than 6,58 mm, as interface for torsion bar pressing, - an external spline interface for connection with Tubular Steering Shaft either in a form of an external 14-tooth spline and with a major diameter of 20,15 mm or more, but not more than 20,30, or in a form of an external 10-tooth spline with a major diameter of 17,53 mm or more, but not more than 17,69 mm, - an outer journal on one shaft end of diameter 11,98 mm or more, but not more than 12 mm, as interface for connection with Lower Assist Shaft, - a twisting lock limiter of the Torsional Bar as external spline, with 2-tooth or 10-tooth external spline. for use in the manufacture of vehicle's steering system	ПОЛША	2551037	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
8708 94 99	Inner tie rod made of carbon steel per SAE J409 Grade 1022 or SAE J403 – GRADE 1022B modified steel, with: - a housing made of JIS G3507/2-SWCH25K-DA low carbon steel, - a ball seat made of polyoxymethylene plastic, - a diameter of tie rod housing 38,75 mm or more, but not more than 39,25 mm, - a distance from the end of tie rod to plane facing rack steering of 291,0 mm or more, but not more than 293,2 mm, - a thread which allows outer tie rod and inner tie rod for connection with dimensions M14 x 1.5, - a ball stud to the end of tie rod distance 271,5 mm or more, but not more than 273,5 mm, for use together with Outer Tie Rod in the vehicle's steering system (1)	ПОЛША	1991194	ново
8708 94 99	Controller cover made of aluminum alloy (per JIS H5302 grade ADC-12) with: - a length of 197,68 mm or more, but not more than 213,87 mm, - a width of 121,23 mm or more, but not more than 129,63 mm, - a height of 11 mm or more, but not more than 27 mm, - a wall thickness of 2 mm or more but not more than 10,3 7 mm, - a 4 to 6 mounting screw holes diameter 4,37 mm or more, but not more than 5 mm, - a 3 to 4 internal heat sink surfaces total height of 2,7 mm or more, but not more than 10,37 mm, for use in the manufacture of vehicle's steering system	ПОЛША	2550817	ново
8708 94 99	Housing rack made with aluminum alloy material (per EN 1706 Grade AC-46000), with: - a length of 568,74 mm or more, but not more than 569,74 mm, - a rack bore diameter of 30,4 mm or more, but not more than 31,4 mm, - an adjuster plug thread with dimensions M39x1, - a boot interface outer diameter of 53,05 mm or more, but not more than 53,30 mm, - a needle bearing bore diameter of 26,95 mm or more, but not more than 26,99 mm,	ПОЛША	2544644	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- a mounting screws bores sizes of 12,3 mm or more, but not more than 14,5 mm, - an assist housing mounting pad thickness of 9,8 mm or more, but not more than 10,0 mm, - two screw holes diameter of 9,44 mm or more, but not more than 9,6 mm and one screw hole diameter of 8,05 or more, but not more than 8,15 mm, - a pinion upper bearing diameter of 47,00 mm or more, but not more than 47,04 mm, - a rack bushings main diameter of 42,9 mm or more, but not more than 43,1 mm, - a rack bushing collar diameter of 46,9 or more, but not more than 47,3 mm, - an insert ring lead diameter of 44,0 mm or more, but not more than 44,4 mm, - an insert ring seating diameter of 44,8 mm or more, but not more than 45,0 mm, - a powerpack support screw thread with dimensions M6x1, for use in the manufacture of vehicle's steering system			
8708 94 99	Shaft Intermediate Steering Assembly with: - a torsional stiffness strength of 25 Nm/degree or more, - a Shaft Assembly Male Tubular made of carbon steel welded tube (per GB/T 699 grade 20), - a Shaft Assembly Female Tubular made of carbon steel welded tube (per GB/T 699 grade 20), - two Spiders Universal Joint made of chromium alloy steel (per GB/T 5216 grade 20CrMnTiH), - a Yoke Steering Gear Clamp made of carbon steel (per GB/T 699 grade 45 or GB/T 699 grade 20), - a Yoke Steering Shaft Clamp made of carbon steel (per GB/T 699 grade 45 or GB/T 699 grade 20), - eight Bearing Assembly Needles, - a length in nominal telescope position of 396 mm or more, but not more than 467 mm,	ПОЛША	2550880	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- a coupling interfaces on both ends with internal serrations to connect with Steering Gear Assembly input shaft and Steering Column Assembly output shaft, - two cardan joints on both sides, - a shaft telescope function with a range of 74 mm or more, but not more than 115 mm, - a telescope sliding load force at zero torque applied of 45 N or less for use in the manufacture of vehicle's steering system			
8708 94 99	Outer tie rod with a housing made of AISI 4137 (SCM435) steel or EN10083/2- C45R + N steel or JIS G4053-SCM435 low alloy steel, with: - ball stud made of EN 10263/4 – 41CrS4 Q + T steel or AISI 4137 (SCM435) steel or EN10083/3-42CrMoS4Q + T steel or JIS G4053-SCM435 low alloy steel, - ball seat made of POM-A plastic or POM plastic, - end of the threaded hole to the ball stud center distance of 124 mm or more, but no more than 194 mm, - ball stud diameter of 21,98 mm or more, but no more than 22 mm, - a threaded hole depth of 40,5 mm or more, but no more than 52 mm with non-metric thread with dimensions M14x1.5, - end cup, - boot seal, - boot seal protector and retaining ring, - lubricant, for use together with Inner Tie Rod in the vehicle's steering system	ПОЛША	2544451	ново
8708 94 99	Lower Assist Shaft made of carbon steel (per GB/T699 grade 45 or JIS G4051 grade S45C) with: - an ultimate torsional strength load of 325 Nm or more and J.A.E.L values of 275 Nm or more, - a length of 66,39 mm or more, but not more than 88,64 mm, - an outer diameter of 27,47 mm or more, but not more than 28,38 mm, - a twisting lock limiter of the Torsional Bar with 2-tooth or 10-tooth internal spline,	ПОЛША	2550954	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- an inner hole of diameter 6,50 mm or more, but not more than 6,58 mm, as interface for Torsion Bar pressing, - an external 26-teeth spline with major diameter 21,18 mm or more but not more than 21,44 mm, as interface to connect with Intermediate Shaft Assembly, - an inner hole of diameter 13,54 mm or more, but not more than 13,58 mm, as interface for mating Upper Assist Shaft, - a knurling on a part of outer surface of major diameter 26 mm or more, but not more than 26,1 mm, as interface for pressing Hub Gear, - with or without an external 24-tooth spline and with a major diameter 24,75 mm or more but not more than 25 mm, as interface for pressing Upper Rotor Assembly, for use in the manufacture of vehicle's steering system			
9503 00 75	Miniature engine: - consisting of a plastic body, - containing a spring, - provides movement of gear shafts with spring tension, for use in the manufacture of the toys under heading 9503 (1)	ТУРЦИЯ	2558768	ново
9503 00 75	Miniature engine: - consisting of a metal body, - allows the gears to rotate by means of the cables it contains transmitting electric current, for use in the manufacture of the toys under heading 9503 (1)	ТУРЦИЯ	2558894	ново
9503 00 75	Miniature engine: - consisting of a plastic body, - with shaft length 11 cm or more but not more than 15,5 cm, - allows the gears to rotate by means of the cables it contains transmitting electric current, for use in the manufacture of the toys under heading 9503 (1)	ТУРЦИЯ	2558847	ново
9503 00 75	Miniature engine driven by mechanical friction: - consisting of a plastic body, - with shaft length 10,5 cm or more but not more than 14,5 cm, - containing a metal disc,	ТУРЦИЯ	2558943	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- creates movement by causing the gears to rotate with the friction force, for use in the manufacture of the toys under heading 9503 (1)			