МИНИСТЕРСТВО НА ФИНАНСИТЕ
АГЕНЦИЯ “МИТНИЦИ”
ЦЕНТРАЛНО МИТНИЧЕСКО УПРАВЛЕНИЕ

ИСКАНИЯ ЗА СУСПЕНДИРАНЕ НА МИТАТА ОТ 1 ЮЛИ 2025 г., ПОСТЪПИЛИ В ГЕНЕРАЛНА ДИРЕКЦИЯ “ДАНЪЧНО ОБЛАГАНЕ И МИТНИЧЕСКИ СЪЮЗ” НА ЕВРОПЕЙСКАТА КОМИСИЯ

1. Настоящият документ представя исканията за въвеждане на автономни мерки за суспендиране на митата на определени химически и индустриални стоки, постъпили в определения срок (15 септември 2024 г.) в ГД “Данъчно облагане и митнически съюз” на Европейската комисия. Исканията се разглеждат в Работна група “Икономически тарифни въпроси” на ЕК и се предлагат за одобрение от Съвета на Европейския съюз. Мерките, които касаят, са за пълно или частично суспендиране на митата от 1 юли 2025 г.
2. Тарифните кодове и текстовите описания на стоките могат да претърпят допълнително уточняване. В настоящия документ са описани всички оригинални искания на държавите членки, както и на Република Турция в рамките на митническия съюз ЕС– Турция.
3. Исканията са подредени по възходящ ред съгласно Комбинираната номенклатура на ЕС.
4. Формулярът за възражение срещу искане от този списък се намира на адрес https://customs.bg/wps/portal/agency/home/info-business/customs-activities/suspending.
5. Български производители, които считат, че тези предложения накърняват икономическите им интереси могат да подадат възражения, като използват формуляр, чийто образец се намира на адрес https://customs.bg/wps/portal/agency/home/info-business/customs-activities/suspending. Срокът за подаване на възражения по нови искания е до 17.12.2024 г. (в Агенция”Митници” – 02.12.2024 г.), а по исканията за продължаване на мерките за суспендирания - до 08.11.2024 г.
6. Коментари по исканията могат да бъдат направени до 17.12.2024 г. за нови искания (в Агенция”Митници” – 02.12.2024 г.) и до 08.11.2024 г. за искания за продължаване на мерките. За целта се използва формулярът за подаване на възражения.

Възраженията и коментарите по исканията за суспендиране на митата, придружени с необходимите мотивационни документи се подават по факс: 02 / 9859 4066.

За допълнителна информация относно суспендирането на митата:
дирекция “Митническа дейност и методология”
02 / 9859 4452 – Бояна Господинова

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
2811 22 00	Silicon dioxide (CAS RN CAS RN 112926-00-8) in powder form with purity by weight of 99 % or more	ТУРЦИЯ	6542070	ново
2903 99 80	4-Bromo-2-fluorobiphenyl (CAS RN 41604-19-7) with a purity by weight of 99 % or more	ИТАЛИЯ	6374666	ново
2909 49 80	2,2'-[oxybis(methylene)]bis[2-ethylpropane-1,3-diol] (CAS RN 23235-61-2) with a purity of 80 % or more by weight	БЕЛГИЯ	6675369	ново
2918 30 00	Ethyl 4-oxopentanoate (CAS RN 539-88-8) with a purity by weight of 98 % or more	БЕЛГИЯ	6674744	ново
2920 29 00	UV absorber, containing: - more than 97 % but not more than 99,8 % by weight of *Bis* (2,4-dicumylphenyl) pentaerythritol diphosphite (CAS RN 154862-43-8) and more than 0,2 % but not more than 2 % triisopropanol amine	БЕЛГИЯ	6700988	ново
2922 29 00	*N,N-bis*(4-methoxybenzyl)amine (CAS RN 17061-62-0) with a purity by weight of 96 % or more	ФРАНЦИЯ	6559853	ново
2924 19 00	Pentanoic acid, 5-(dimethylamino)-2-methyl-5-oxo-,methyl ester (CAS RN 1174627-68-9) with a purity by weight of 70 % or more	ФРАНЦИЯ	6569422	ново
2924 98 59	Magnesium 2-aminoacetate (IUPAC) with a purity by weight of 100 %	ИРЛАНДИЯ	6532635	ново
2925 29 00	Aqueous solution consisting by weight of: - more than 30 % but not more than 36 % of *N,N*-dibutyl[bis(diethylamino)]methaniminium chloride (CAS RN 89450-30-6) not more than 14 % of sodium chloride (CAS RN 7647-14-5)	БЕЛГИЯ	1966069	ново
2932 99 00	2-butyl-3-(4-hydroxybenzoyl)benzofuran (CAS RN 52490-15-0) with a purity by weight of 99 % or more	ФРАНЦИЯ	6560077	ново
2933 39 99	(*R*)-(-)-3-amino-1-boc-piperidine (CAS RN 188111-79-7) with a purity by weight of 96 % or more	ФРАНЦИЯ	6559820	ново
2933 39 99	2,4-dichloro-3-nitropyridine (CAS RN 5975-12-2) with a purity by weight of 99 % or more	ФРАНЦИЯ	6559904	ново
2933 59 95	Ruxolitnib phosphate (INNM) (CAS RN 1092939-17-7) with a purity by weight of 99 % or more	ФРАНЦИЯ	6559961	ново
2933 99 80	*N,N*-Dimethyl-*N*-octadecyl-1-octadecanaminium-(sp-4-2)-[29h,31*H*-phthalocyanine-2-sulfonato-n29,n30,n31,n32]cuprate(CAS RN 70750-63-9) with a purity by weight of 90 % or more.	ГЕРМАНИЯ	6501799	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
2933 99 80	2-(2*H*-Benzotriazole-2-yl)-6-(2-phenylpropane-2-yl)-4-(2,4,4-trimethylpentane-2-yl)phenole (CAS RN 73936-91-1) with a purity by weight of 97 % or more	ГЕРМАНИЯ	6408059	ново
2933 99 80	5*H*-Pyrazolo[4,3-c]pyridine-5-carboxylic acid, 3-amino-2-(4-fluoro-3,5-dimethylphenyl)-2,4,6,7-tetrahydro-4-methyl-, 1,1-dimethylethyl ester, (4*S*) (CAS RN 2212021-59-3) with a purity by weight of 99 % or more	ИТАЛИЯ	6407956	ново
2933 99 80	Poly(oxy-1,2-ethanediyl),alpha-[3-[3-(2*H*-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy-phenyl]-1-oxopropyl]-omega-hydroxy- and poly(oxy-1,2-ethanediyl),alpha-[3-[3-(2*H*-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy- phenyl]-1-oxopropyl]-omega-[3-[3-(2*H*-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy] with a purity by weight of 98 % or more	БЕЛГИЯ	6676141	ново
2933 99 80	2-(2*H*-benzotriazol-2-yl)-6-(1-methyl-1-phenylethyl)-4-(1,1,3,3-tetramethylbutyl) phenol (CAS RN 73936-91-1) with a purity by weight of 99 % or more	БЕЛГИЯ	6700668	ново
2933 99 80	6-O-*tert*-butyl 4a-O-methyl (4aR)-1-(4-fluorophenyl)-4,5,7,8-tetrahydropyrazolo[3,4-g]isoquinoline-4a,6-dicarboxylate (CAS RN 864972-21-4) with a purity by weight of 95 % or more	ИСПАНИЯ	6469177	ново
2934 99 90	*Bis*-4*H*-3,1-benzoxazin-4-one, 2,2'-(1,4-phenylene)-(CAS RN 18600-59-4)	БЕЛГИЯ	6704545	ново
2934 99 90	2-[4,6-*bis*({[1,1'-biphenyl]-4-yl})-1,3,5-triazin-2-yl]-5-[(2-ethylhexyl)oxy]phenol (CAS RN 204583-39-1)	БЕЛГИЯ	6704858	ново
3204 13 00	Mixture of: - 25 % or more but not more than 40 % of Colourant C.I. Basic Blue 3 (CAS RN 33203-82-6) and - 25 % or more but not more than 40 % of C.I. Basic Blue 159 (CAS RN 105953-73-9) and preparations based thereon	ТУРЦИЯ	6819860	ново
3204 15 00	Vat blue 1 solution containing by weight: - 40 % of a mixture (CAS RN 207692-02-2) of Vat Blue 1 reduced K-salt (CAS RN 835912-68-0) and Na-Salt (CAS RN 894-86-0) in the ratio of 3:2; - 0,5 % of Napthalenesulfonic acid, polymer with formaldehyde, sodium salt (CAS RN 9084-06-4);	ТУРЦИЯ	6633361	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- 2,4 % of Potassium hydroxide (CAS RN 1310-58-3); - 1,6 % of Sodium hydroxide (FKS) (CAS RN 1310-73-2); 55,5 % of Water (CAS RN 7732-18-5)			
3204 17 00	Colourant C.I. Pigment Yellow 110 (CAS RN 5590-18-1) and preparations based thereon with a colourant C.I. Pigment Yellow 110 content of 90 % or more by weight	НИДЕРЛАНДИЯ	6905336	ново
3204 17 00	Colourant C.I. Pigment Yellow 62 (CAS RN 12286-66-7) and preparations based thereon with a colourant C.I. Pigment Yellow 62 content of 90 or more by weight	НИДЕРЛАНДИЯ	6905292	ново
3204 17 00	Colourant C.I. Pigment Yellow 17 (CAS RN 4531-49-1) and preparations based thereon with a colourant C.I. Pigment Yellow 17 content of 90 % or more by weight	НИДЕРЛАНДИЯ	6905230	ново
3204 17 00	Colourant C.I. Pigment Yellow 13 (CAS RN 5102-83-0) and preparations based thereon with a colourant C.I. Pigment Yellow 13 content of 50 % or more by weight	ИРЛАНДИЯ	6532547	ново
3204 17 00	Colourant C.I. Pigment Yellow 139 (CAS RN 36888-99-0) and preparations based thereon with a colourant C.I. Pigment Yellow 139 content of 90 % or more by weight	НИДЕРЛАНДИЯ	6905393	ново
3204 17 00	Colourant C.I. Pigment Yellow 174 (CAS n 78952 -72-4) and preparations based thereon with a colourant C.I. Pigment Yellow 174 content of 50 % or more by weight.	ИРЛАНДИЯ	6542652	ново
3204 17 00	Colourant C.I. Pigment Yellow 147 (CAS RN 4118-16-5) and preparations based thereon with a colourant C.I. Pigment Yellow 147 content of 90 % or more by weight	НИДЕРЛАНДИЯ	6905498	ново
3204 17 00	Colourant C.I. Pigment Red 146 (CAS RN 5280-68-2) and preparations based thereon with a colourant C.I. Pigment Red 146 content of 90 % or more by weight	ГЕРМАНИЯ	6501729	ново
3204 17 00	Colourant C.I. Pigment Red 264 (CAS RN 88949-33-1) and preparations based thereon with a colourant C.I. Pigment Red 264 content of 90 % or more by weight	ГЕРМАНИЯ	6501677	ново
3204 17 00	Colourant C.I. Pigment Red 2 (CAS RN 6041-94-7) and preparations based thereon with a colourant C.I. Pigment Red 2 content of 90 % or more by weight	ГЕРМАНИЯ	6325899	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
3204 17 00	Colourant C.I. Pigment Yellow 65 (CAS RN 6528-34-3) and preparations based thereon with a colourant C.I. Pigment Yellow 65 content of 90 % or more by weight	ГЕРМАНИЯ	6325804	ново
3204 17 00	Colourant C.I. Pigment Red 177 (CAS RN 4051-63-2) and preparations based thereon with a colourant C.I. Pigment Red 177 content of 90 % or more by weight	ГЕРМАНИЯ	6325563	ново
3204 17 00	Colourant C.I. Pigment Blue 29 (CAS RN 57455-37-5) and preparations based thereon with a colourant C.I. Pigment Blue 29 content of 90 % or more by weight	БЕЛГИЯ	6701125	ново
3204 17 00	Colourant C.I. Pigment Yellow 168 (CAS RN 71832-85-4) and preparations based thereon with a colourant C.I. Pigment Yellow 168 content of 90 % or more by weight	НИДЕРЛАНДИЯ	6905728	ново
3204 17 00	Colourant C.I. Pigment Red 112 (CAS RN 6535-46-2) and preparations based thereon with a colourant C.I. Pigment Red 112 content of 90 % or more by weight	ГЕРМАНИЯ	6325339	ново
3204 17 00	Colourant C.I. Pigment Yellow 180 (CAS RN 77804-81-0) and preparations based thereon with a colourant C.I. Pigment Yellow 180 content of 90 % or more by weight	БЕЛГИЯ	6704383	ново
3204 17 00	Colourant C.I. Pigment Red 264 (CAS RN 88949-33-1) and preparations based thereon with a colourant C.I. Pigment Red 264 content of 90 % or more by weight	ГЕРМАНИЯ	6501301	ново
3204 17 00	Colourant C.I. Pigment Red 122 (CAS RN 980-26-7) and preparations based thereon with a colourant C.I. Pigment Red 122 content of 90 % or more by weight	ГЕРМАНИЯ	6299757	ново
3204 17 00	Colourant C.I. Pigment Yellow 183 (CAS RN 65212-77-3) and preparations based thereon with a colourant C.I. Pigment Yellow 183 content of 90 % or more by weight	ГЕРМАНИЯ	6325279	ново
3204 19 00	Colourant C.I. Solvent Yellow 114 (CAS RN 17772-51-9) and preparations based thereon with a colourant C.I. Solvent Yellow 114 content of 90 % or more by weight	НИДЕРЛАНДИЯ	6905681	ново
3204 19 00	Colourant C.I. Solvent Red 52 (CAS RN 81-39-0) and preparations based thereon with a colourant C.I. Solvent Red 52 content of 90 % or more by weight	НИДЕРЛАНДИЯ	6905530	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
3204 19 00	Colourant C.I. Solvent Red 135 (CAS RN 71902-17-5) and preparations based thereon with a colourant C.I. Solvent Red 135 content of 90 % or more by weight	НИДЕРЛАНДИЯ	6905598	ново
3206 49 70	Colourant C.I. Pigment Yellow 164 (CAS RN 68412-38-4) and preparations based thereon with a colourant C.I. Pigment Yellow 164 content of 90 % or more by weight	ГЕРМАНИЯ	6325697	ново
3809 91 00	Water based antimony pentoxide solution containing by weight 25 % or more but not more than 50 % of diantimony pentoxide (CAS RN 1314-60-9)	ТУРЦИЯ	6559753	ново
3812 39 10	Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8)	БЕЛГИЯ	6700840	ново
3812 39 90	Reaction mass of - decanedioic acid, *bis*(1,2,2,6,6-pentamethyl-4-piperidinyl) ester and decanedioic acid, (1,2,2,6,6-pentamethyl-4-piperidinyl) methyl ester (CAS RN 1065336-91-5)	БЕЛГИЯ	6700716	ново
3812 39 90	UV stabilizer based on - reaction mass of Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- and Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1- oxopropoxy] (CAS RN 400-830-7) with a purity by weight of 55 % or more, but not more than 75 %, - Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat (CAS RN 41556-26-7) with a purity by weight of 15 % or more, but not more than 35 %, and Methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacat (CAS RN 82919-37-7) with a purity by weight of 5 % or more, but not more than 15 %	ГЕРМАНИЯ	6408129	ново
3812 39 90	UV stabilizer based on a - reaction mass of branched and linear C7-C9 alkyl 3-[3-(2*H*-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates (CAS RN 127519-17-9) with a purity by weight of 40 % or more, but not more than 60 %, and a reaction mass of decanedioic acid, 1,10-*bis*[2,2,6,6-tetramethyl-1-(octyloxy)-4-piperidinyl] ester and decanedioic acid, 1,8-octanediylbis[oxy(2,2,6,6-	ГЕРМАНИЯ	6408250	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	tetramethyl-1,4-piperidinediyl)] *bis*[2,2,6,6-tetramethyl-1-(octyloxy)-4-piperidinyl] (CAS RN 29757-67-1) with a purity by weight of 40 % or more, but not more than 60 %			
3812 39 90	Ethyl 4-[[(methylphenylamino)methylene]amino] benzoate (CAS RN 57834-33-0) with a purity of 99 % or more by weight	БЕЛГИЯ	6701073	ново
3812 39 90	Reaction mass of Octyl-3-[3-tert-butyl-4-hydroxy-5-(5-chloro-2Hbenzotriazole-2-yl) phenyl] propionate (CAS RN 83044-89-7) and 2-Ethylhexyl-3-[3-tert-butyl-4-hydroxy-5-(5-chloro-2H-benzotriazole-2-yl) phenyl] Propionate (CAS RN 83044-90-0)	БЕЛГИЯ	6700790	ново
3812 39 90	Stabiliser containing: - 75 % or more but not more than 95 % by weight of 2-(4,6-*bis*(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-hydroxyphenol with ((C10-16, rich in C12-13 alkyloxy) methyl) oxyrane (CAS RN 153519-44-9) and 5 % or more but not more than 25 % by weight of 1-methoxy-2-propanol (CAS RN 107-98-2)	БЕЛГИЯ	6675920	ново
3812 39 90	Light stabilisers containing a mixture of - benzenepropanoic acid, 3-(2*H*-benzotriazole-2-yl)-5-(1,1-di-methylethyl)-4-hydroxy-,C7-9 branched and linear alkyl esters (CAS RN 127519-17-9) in an amount of 92 % or more by weight and 1-methoxy-2-propyl acetate (CAS RN 108-65-6) of more than 2 % but not more than 8 % by weight	БЕЛГИЯ	6676427	ново
3815 90 90	Catalytic preparations for fluid catalytic cracking, in the form of powder, consisting of a mixture of one or more of the following active substances: - calcium carbonate (CAS RN 471-34-1), - copper oxide (CAS RN 1217-38-0), - iron oxide (CAS RN 1309-37-1), - aluminium magnesium vanadium oxide (CAS RN 70621-8-0), - aluminium phosphate (CAS RN 7784-30-7), - cerium oxide (CAS RN 1306-38-3), and one or more of the following inert substances: - magnesium oxide (CAS RN 1309-48-8), - aluminium oxide (CAS RN 1344-28-1), - kaolin (CAS RN 1332-58-7)	НИДЕРЛАНДИЯ	6569700	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
3824 99 92	Mixture containing by weight: - 55 % or more but not more than 65 % of (2*S*,3*S*,4*S*,5*R*,6*R*)-2-(((2*R*,3*R*,5*S*,6*R*)-4-(((2*R*,3*S*,4*S*,5*R*,6*R*)-3-acetoxy-4,5-*bis*(benzyloxy)-6-((benzyloxy)methyl)tetrahydro-2*H*-pyran-2-yl)oxy)-3,5-*bis*(benzyloxy)-6-(4-methoxy-4-oxobutoxy)tetrahydro-2H-pyran2yl)methoxy)-6-((((2*S*,3*S*,4*S*,5*R*,6*R*)-3-acetoxy-4,5-bis(benzyloxy)-6-((benzyloxy)methyl)tetrahydro-2*H*-pyran-2-yl)oxy)methyl)tetrahydro-2*H*-pyran-3,4,5-triyl tribenzoate (CAS RN 12334475-58-5), 35 % or more but not more than and 45 % of tolu-ene (CAS RN 108-88-3)	ФРАНЦИЯ	6560008	ново
3824 99 96	Preparation containing by weight: - 30 % or more, but not more than 60 % of 3a,4,4a,5,8,8a,9,9a-octahydro-1*H*-4,9:5,8-dimethanocyclopenta[b]naphtalene (CAS RN 7158-25-0), - 10 % or more, but not more than 50 % of 3a,4,7,7a-tetrahydro-4,7-methanoindene (CAS RN 77-73-6) and whether or not 10 % or more, but not more than 40 % of petroleum hydrocarbon resin (CAS RN 68132-00-3)	БЕЛГИЯ	6704901	ново
3824 99 96	Vulcanizing material containing by weight of - 78% or more but not more than 82 % insoluble sulphur (CAS RN 9035-99-8), - 18% or more but not more than 22 % naphthenic oil (CAS RN 64742-52-5), and less than 0,2 % methyl styrene (CAS RN 98-83-9)	ТУРЦИЯ	6542127	ново
3824 99 96	Preparation containing by weight: - 80 % or more, but not more than 90 % of 3a,4,7,7a-tetrahydro-4,7-methanoindene (CAS RN 77-73-6), and - Whether or not but not more than 10 % of 3a,4,4a,5,8,8a,9,9a-octahydro-1H-4,9:5,8-dimethanocyclopenta[b]naphtalene (CAS RN 7158-25-0), and 0,5 % or more, but not more than 3 % of 2,6-di-tert-butyl-p-cresol (CAS RN 128-37-0)	БЕЛГИЯ	6704973	ново
3824 99 96	Butyl methacrylate (CAS RN 97-88-1) of a purity by weight of 99 % or more and methyll methacrylate (CAS RN 80-62-6) of a purity by weight of more than 0,1 % but not more than 0,5 %	БЕЛГИЯ	6675420	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
3824 99 96	Vulcanizing material containing by weight - 20 % naphthenic oil (CAS RN 64742-52-5), 80 % insoluble sulfur containing (CAS RN 9035-99-8)	ТУРЦИЯ	6542168	ново
3906 90 90	Acrylonitrile styrene acrylate copolymer in the form of granules containing: - 48 % styrene, - 22 % scrylonitrile, - 29 % sutylacrylat, and 1 % dihydrodicyclopentadienyl acrylate	ГЕРМАНИЯ	6548275	ново
3907 29 20	- Glycerol (CAS RN 31694-55-0), ethoxylated based polyol with a hydroxyl number of 541 or more but not more than 587	ТУРЦИЯ	7015635	ново
3907 29 20	Poly[oxy(methyl-1,2-ethanediyl)], α-hydro-ω-hydroxy-, ether with b-D-fructofuranosyl a-Dglucopyranoside (CAS RN 9049-71-2)	ТУРЦИЯ	6536442	ново
3907 29 99	Polyethylene glycol with an ethylene oxide chain length of not more than 30, having butyl-2-cyano 3-(4-hydroxyphenyl) acrylate end groups (CAS RN 780763-40-8)	БЕЛГИЯ	6704740	ново
3911 10 00	Combination of organic compounds, predominantly 100 % hydrocarbons, obtained as a fraction of the extract from solvent extraction of the residue	ТУРЦИЯ	6542237	ново
3911 10 00	Petroleum resin containing by weight - more than 98 % asphalt (CAS RN 8052-42-4), less than 2 % Hydrated Amorphous Silica (CAS RN 112926-00-8)	ТУРЦИЯ	6542308	ново
3920 30 00	Biaxially oriented, non-cellular high impact polystyrene (HIPS) foil in rolls whether or not printed with: - a thickness of 0,229 mm or more but not more than 0,279 mm, - an opaque with titanium dioxide content of 3 % or more but not more than 3.5 %, - a width of 82,05 mm or more but no more than 83,05 or 107,45 or more but no more than 108,45 mm, - a water mobility of 20 degrees or more but not more than 23 degrees, - a reflectance of 57 % or more, - a waviness of not more than 1 mm out of flatness, a super hydrophobic coating chemically neutral and non-reactive to other substances, especially to chemical reagents intended for urine diagnostics	ПОЛША	6633644	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
3920 62 19	Three-layer plastic film consisting of a 15 µm fluorinated polymer (FCC) (EVA) layer, a 275 µm polyethylene terephthalate (PET) layer and a 25 µm fluorinated polymer (FCC) layer: - with a total thickness of 300-330 µm, - with a tensile strength of ≥ 375 N/cm in both the longitudinal and transverse directions (ASTM D-882), - with a low thermal shrinkage of ≤ 1,0 % at 150 °C for 30 minutes, - a low water vapour permeability of ≤ 2,5 g/m²²•d, and - with a high breakdown voltage ≥18 kV and a partial discharge voltage ≥1500 VDC (BG/T 123542.2-2009) to be used as a protective layer on the back of photovoltaic modules, to provide insulation and protection against external influences.	СЛОВЕНИЯ	6569498	ново
3920 99 21	Polyamide film with a length of 100 µm or more but not more than 200 µm	ТУРЦИЯ	6536343	ново
7007 19 80	A tempered glass in a circular shape with: - a light transmittance of 34,2 % or more but not more than 37,8 %, - a diameter of 477,2 mm or more but not more than 477,8 mm, - a thickness of 2,9 mm or more but not more than 3,5 mm, - a weight of 1345 g or more but not more than 1445 g, - 3-zone structure including Euro Deep Gray colour printed zone, for the cover of door assembly in washing machines (1)	ПОЛША	6663234	ново
7019 80 10	A vacuum insulation panel consisting of a gas-tight housing surrounding a rigid core devoid of air: - with fiberglass or chopped fiberglass filling, - a thickness of 5,6 mm or more but not more than 20,4 mm, - a length of 195 mm or more but not more than 1 835 mm, - a width of 155 mm or more but not more than 545 mm, - a thermal conductivity lower than 2,5 mW/mK, - an internal pressure of 0,1 Pa, ambient temperature during operation of -50 °C or more but not more than 70 °C	ПОЛША	6663116	ново
7606 91 00	Aluminium cutout of a rounded shape made from non-alloy aluminium AA 1050: - laminated with a layer of fleece or hot-melt adhesive,	ПОЛША	6633432	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- with a total thickness of 0.9 mm or more, but not more than 1.1 mm, - with an aluminum layer thickness of 0.8 mm or more, but not more than 0.9 mm, - embossed with a geometric pattern lacquered and coated with a protective layer			
8406 81 00	Industrial steam turbine with: - an output of 40 MW or more but not more than 60 MW, - designed for a pressure of not more than 140 bar and a temperature of not more than 540 ° C, equipped with double seat valves on the live steam side which are operated with a hydraulic servo of not more than 30 bar	ГЕРМАНИЯ	6501845	ново
8409 99 00	Die cast aluminium housing for electronic throttle control or exhaust gas recirculation systems: - high pressure-casted of EN AC-46000 aluminium, - shot-blasted and machined, - with a height of 100 mm or more but not more than 135 mm, - with a width of 115 mm or more but not more than 150 mm, with a weight of 210 g or more but not more than 465 g	ПОЛША	2556095	ново
8412 21 80	Hydraulic actuators of a kind used in the arms of machines for handling cargo containers: - with a weight of 827 kg or more but not more than 935 kg, - with a diameter of 250 mm or more but not more than 330 mm, - with a length of 3480 mm or more but not more than 4115 mm, - with a stroke of 2750 mm or more but not more than 3180 mm, - adapted to work with hydraulic oil at a working pressure of 23 MPa, whether or not with a maintenance-free bearing without the need for lubrication	ПОЛША	6633775	ново
8412 21 80	Hydraulic actuators of a kind used in the machines for handling cargo containers: - with a weight of 45 kg or more but not more than 57 kg, - with a diameter of 119 mm or more but not more than 149 mm, - with a length of 779 mm or more but not more than 1141 mm, - with a stroke of 450 mm or more but not more than 610 mm,	ПОЛША	6662606	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- adapted to work with hydraulic oil at a working pressure of 22 MPa or more but not more than 23 Mpa, whether or not with a maintenance-free bearing without the need for lubrication			
8414 30 20	Hermetic refrigeration compressor for R-600a as refrigerant: - not charged with refrigerant, - pre-charged with the lubricant oil with oil charge 150 cm3 or higher, but not higher than 170 cm3, - with a brushless DC electric motor (BLDC), - having right side suction connection with inner diameter of 6,44 mm or more, but not more than 6,64 mm and right side discharge connection of inner diameter 4,85 mm or more, but not more than 5,05 mm, - with displacement 9,93 cm3 or higher, but not higher than 10,13 cm3, - running at 1 300 rpm or faster, but not faster than 4 500 rpm, with a cooling capacity of 80 W or higher, but not higher than 273 W	ПОЛША	6662813	ново
8414 30 89	Compressor for motor vehicle air conditioning system: - electrical compressor with a power output of more than 0,4 kW but not exceeding 10 kW for use in the manufacture of motor vehicles under Chapter 87 (1)	ТУРЦИЯ	7128266	ново
8418 99 90	An evaporator being a type of heat exchanger, consisting of aluminium pipes with copper ends enclosed with aluminium radiators: - measuring 403 x 276 x 70 mm or more, but not more than 464 x 399 x 83 mm, - with a total weight of a set of 236 g or more, but not more than 1 010 g, - with a fixed sensor, - with noise absorber, - with 2, 5 or 7 control and power connection pins terminated with sensor temperature, heater or fuse type of socket for use in the manufacture of freezers or refrigerators (1)	ПОЛША	6662970	ново
8431 20 00	Concrete counterweights of a kind used in machines for handling transport containers and forklifts with: - a weight of 2 100 kg or more but not more than 13 000 kg, - a height of 30 cm or more but not more than 110 cm,	ПОЛША	6662678	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- a length of 160 cm or more but not more than 260 cm, - a width of 195 cm or more but not more than 330 cm, - smoothed edges, - colored pain coated, whether or not encased steel sheet with a thickness of 5 mm or more			
8431 20 00	Container spreader of a kind used for lifting empty 20' and 40' cargo containers: - without an integrated carriage, - suitable for machines with a load capacity of not more than 11 000 kg, - designed to carry one or two containers at a time, - with a top or side mounting, - with an anti-corrosion layer coated, with a weight of 3 200 kg or more but not more than 4 000 kg	ПОЛША	6662758	ново
8481 80 59	Solenoid valve of combustion engine oil pump for regulating the amount of oil in the pump: - with cable with length of 550 mm or more but not more than 700 mm with electrical connector - with an operating pressure of not more than 5.5 bar, - with an operating voltage of 9 VDC or more but not more than 16 VDC, - with a valve's base width of 22 mm but not more than 27 mm, - with a valve's length of 55 mm but not more than 110 mm, for use in the manufacture of engines of motor vehicles (1)	СЛОВАКИЯ	6501431	ново
8483 10 95	Assy shaft of DRUM for torque transmission, made of steel (per SM45C for shaft standard and STS430 for ring standard) with: - a length of 137,8 mm or more but not more than 138,2 mm - an outer diameter of 23 mm or more but not more than 48,025 mm, - a weight of 1,0245 kg or more but not more than 1,0445 kg, - a hardness of shaft 40 HRC or more but not more than 50 HRC, - a hardness of ring 90 HRB or more, but no more than 120 HRB, an external 37-teeth spline with major diameter of 41 mm or more but not more than 48 mm	ПОЛША	6663039	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
8501 31 00	Electric brushless direct current motor finished with biocompatible materials such as stainless steel according to specification 17-4 PH or type 303, 316L, 400 with: - a three-phase winding, - an output power not exceeding 280 W, - a length with gearhead of 116,1 mm or more but not more than 117,2 mm, - an external diameter of 13,86 mm or more but no more than 13,92 mm, - a maximum torque of motor with gearhead 246,6 mNm in 25°C, - a no-load radial speed of motor with gearhead at 24 V-25°C 9 900 rpm, - a weight of motor with gearhead of 70,5 g or more but not more than 71,5 g, - a resistance to peak temperature of 140°C or more (non-operating), - a maximal air leak between shaft and shaft seals of 15 Pa/s at given 2 Bars of pressure, - 14 functional pins for power and control purpose, - a flexible printed circuit with length of 245 mm but no longer than 255 mm with mounted 8 pin male connector for use in the manufacture of medical devices with right-left rotation and oscillation function (1)	ПОЛША	6633590	ново
8501 31 00	Brushless DC electric motor, with: - a rated voltage DC310V PWM Voltage, - a rated power of 350 W or more but not more than 368 W, - an input power of 500 W or more but not more than 550 W, - output power of 350 W or more but not more than 400 W, - an external diameter without bracket connector and pulley of 143,2 mm or more but not more than 143,8 mm, - a rated speed of 16300 rpm or more but not more than 16500 rpm, - a weight of 2,33 kg or more but not more than 2,40 kg, a pulley	ПОЛША	6662876	ново
8501 51 00	Electric permanent magnet synchronous motor with: - an output power of 550 W,	ПОЛША	6633467	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- a rotor containing 8 poles generated by permanent magnets made with a composition of neodymium-iron-boron (per GB/T 13560 standard) enclosed in polyethylene cover, - an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm, - terminals located across the radius 32,5 mm and separated by an angle of 21,8°, - a motor housing made of ADC12 or AC46000 aluminium alloy die casting with composition of aluminium-silicon-copper (per JIS H5302 or EN1706 standard), - a back EMF constant (Ke) of 0,03306 V-sec/rad or more but no more than 0,03654 V-sec/rad, - a back EMF harmonics order - 5th of no more than 0,38 % (of fundamental) and 7th of no more than 0,25 % (of fundamental), - a cogging torque of no more than 13 mNm, - a friction torque in ambient temperature of no more than 22 mNm, a maximum temperature of motor operation not more than 200 °C			
8501 51 00	Electric permanent magnet synchronous motor with: - an output power of 600 W, - a rotor containing 8 poles generated by permanent magnets made of composition of iron, neodymium, boron and dysprosium enclosed in aluminium cover, - an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm, - terminals located across the diameter 59,2 mm and separated by an angle 30,0°, - a housing made of electrogalvanized steel (per JIS G3313 Grade SECE standard) using a deep-drawing stamping process, - a diameter of 88,600 mm or less but no less than 88,546 mm at the motor-system assembly interface, - a back EMF constant (Ke) of 0,03277 V-sec/rad or more but no more than 0,03623 V-sec/rad,	ПОЛША	6633489	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- • a back EMF harmonics order - 5th of no more than 0,35 % (of fundamental) and 7th of no more than 0,30 % (of fundamental), - a cogging torque of no more than 12 mNm, - a friction torque in ambient temperature of no more than 23 mNm, a maximum temperature of motor operation not more than 200 °C			
8501 52 20	Electric permanent magnet synchronous motor with: - an output power of 850 W, - a rotor containing 8 poles generated by permanent magnets made with a composition of neodymium-iron-boron (per GB/T 13560 standard) enclosed in polyethylene cover, - an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm, - terminals located across the radius 26,2 mm and separated by an angle 30,0°, - a housing made of ADC12 or AC46000 aluminium alloy die casting with composition of aluminium-silicon-copper (per JIS H5302 or EN1706 standard) and anodized coating (per ASTM B580 type E standard), - a back EMF constant (Ke) of 0,04009 V-sec/rad or more but no more than 0,04431 V-sec/rad, - a back EMF harmonics order - 5th of no more than 0,36 % (of fundamental) and 7th of no more than 0,24 % (of fundamental), - a cogging torque of no more than 20 mNm, - a friction torque in ambient temperature of no more than 26,5 mNm, a maximum temperature of motor operation not more than 200 °C	ПОЛША	6633548	ново
8503 00 99	Pressure casted rotor front plate or cover of an electric supercharger: - of EN AC-46000 aluminium, - shot-blasted and machined, - with an HBW of 60 or more (2,5/62,5, according to ISO 6506), - with a tensile strength of 240 N/mm2 or more, - with a height of 22 mm or more but not more than 26 mm, - with a diameter of 128 mm or more but not more than 136 mm, with a weight of 220 g or more but not more than 250 g	ПОЛША	2556164	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
8505 11 10	Magnetized upper rotor made with steel stack according to standards ASTM A677-07 grade 47F180 or JIS C 2552 Grade 50A310, with: - twelve permanent magnets made with neodymium-iron-boron, enclosed in stamped steel stack ring, - a residual induction value 1,21 T or more but not more than 1,32 T. at 25° C, - an inner diameter of 22,735 mm or more but no more than 22,835 mm, - an outer diameter of 30,725 mm or more but no more than 38,025 mm for use in the manufacture of vehicle's steering system (1)	ПОЛША	2544759	ново
8507 60 00	Modules used for the assembly of lithium-ion electric accumulators: - contains 12 or more cells but not more than 36 cells, - with a nominal capacity of 51 Ah per cell, - with a nominal voltage of 60 V or more, but not more than 120 V, - with a weight of 18 kg or more but not more than 36 kg, - with a width of 100 mm or more but no more than 220 mm, - with a height of 80 mm or more but no more than 180 mm, - with a length of 700 mm or more but no more than 1 200 mm, for use in the manufacture of motor vehicles of subheading 8703.60 (1)	ТУРЦИЯ	7128403	ново
8507 60 00	Rechargeable lithium-ion battery pack: - with a length of 1 050 mm or more but not exceeding 1 070 mm, - with a width of 624 mm or more but not exceeding 636 mm, - with a height of 235 mm or more but not exceeding 255 mm, - with a weight of 210 kg or more but not exceeding 230 kg, - with a nominal capacity of 215 Ah or more but not exceeding 315 Ah, - with power not exceeding 45 kWh, - with a nominal voltage of 100 V or more but not exceeding 175 V, with a capacity not exceeding 400 Ah	ТУРЦИЯ	7128192	ново
8507 60 00	Lithium ion battery: - contains 48 or more cells but not more than 84 cells - consists of 2 or more modules but not more than 4 modules - with a nominal capacity of 4,08 Ah per cell - with a nominal voltage of 200 V or more, but not more than 426 V	ТУРЦИЯ	7128336	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- with a weight of 9 kg or more but not more than 48 kg - with a width of 280 mm or more but no more than 360 mm, - with a height of 150 mm or more but no more than 220 mm, - with a length of 600 mm or more but no more than 1 200 mm, for use in the manufacture of motor vehicles of Chapter 87 (1)			
8537 10 91	Electronic assembly containing: - a microprocessor, - a programmable memory and other electronic components mounted on a printed circuit, - with or without light-emitting diode (LED) or Thin Film Transistor (TFT) or Liquid Crystal Display (LCD technology) indicators for use in the manufacture of products of subheadings 7321 11, 8414 60, 8418 10, 8418 21, 8418 29, 8418 40, 8421 12, 8422 11, 8450 11, 8450 12, 8450 20, 8450 19, 8451 21, 8451 29 and 8516 60 (1)	УНГАРИЯ	6633310	ново
8544 30 00	The wire harness ensures the board communication with the other components of the car's EPS (Electrical Power Steering) system with: - a length of 170 mm or more but not more than 301 mm, - an outer diameter of 4,5 mm or more but not more than 5,20 mm, - an operating temperature of - 40°C or more but not more than 125°C, - exposed wire end with a maximum diameter of 0,8 mm after tinning, - connectors, - a gold or tin plating terminals, an XL-PE or TPE-E wire insulation material	ПОЛША	6633735	ново
8544 42 90	Wire harness with a 26-PIN or 28-PIN wire to board connectors in crimping technology for the transmission of signals and/or electrical power bound by rubber or vinyl or electrical tape or conduit or a weave of extruded string or a combination of thereof for connection of power supply with main printed (circuit) board assembly (PBA) and electrical components of refrigerator or washing machine (1)	ПОЛША	6663164	ново
8708 40 20	Transmission assembly consisting of: - double pinion type planetary gear shifting mechanism, - sport sequential shiftmatic system that does not have lower than 7-speed and not higher than 10-speed	ТУРЦИЯ	6502232	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- with the dimensions of: - a width of 280 mm or more but no more than 470 mm, - a height of 350 mm or more but no more than 595 mm, - a length of 410 mm or more but no more than 690 mm, - a weight of 70 kg or more but no more than 110 kg, for use in the manufacture of motor vehicles of Chapter 87 (1)			
8708 40 50	Transmission assembly which houses 3 other shafts inside it and offers a rotating switch for shift position, consisting of: - cast aluminum body, - differential gear, - 2 electrical machines and gears - with the dimensions of: - a width of 280 mm or more but no more than 470 mm, - a height of 350 mm or more but no more than 595 mm, - alength of 410 mm or more but no more than 690 mm, for use in the manufacture of motor vehicles of Chapter 87 (1)	ТУРЦИЯ	6502103	ново
8708 91 35	Radiators with corrosion protection, for pressures up to 150 PSI (1034 kPa) with individual replaceable, cooling tubes in brass or copper for use in the production of engine and charge air cooling with a weight of 265 kg or more but not more than 599 kg	ШВЕЦИЯ	6469652	ново
8708 94 99	Torsion bar as part of the steering column made of carbon alloy steel (per SAE J1268, grade 5160H of modified chemistry for carbon content of 0,53 or more, but not more than 0,56) with: - a shaft torsional stiffness of 2,5 Nm/degree or more but not more than 2,7 Nm/degree, - a length of 107,75 mm or more but no more than 108,25 mm, - an outer diameter of 6,38 mm or more but no more than 6,42 mm, - two external 18-tooth splines on both shaft ends with a major diameter of 6,70 mm or more but - no more than 6,85 mm, as interface to pressing with matting input and output shafts, - entire surface shot peened for use in the manufacture of vehicle’s steering system (1)	ПОЛША	2555819	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
8708 94 99	Outer tie rod with a housing made of AISI 4137 (SCM435) steel or EN10083/2- C45R + N steel or JIS G4053-SCM435 low alloy steel, with: - a ball stud made of EN 10263/4 – 41CrS4 Q + T steel or AISI 4137 (SCM435) steel or - EN10083/3-42CrMoS4Q + T steel or JIS G4053-SCM435 low alloy steel, - a ball seat made of polyoxymethylene plastic, - an end of the threaded hole to the ball stud center distance of 124 mm or more but no more than 194 mm, - a ball stud diameter of 21,98 mm or more but no more than 22 mm, - a threaded hole depth of 40,5 mm or more but no more than 52 mm with dimensions M14x1,5, - a boot seal, - a boot seal protector and retaining ring, - lubricant, for use in the in manufacture of vehicle's steering system (1)	ПОЛША	2544451	ново
8708 94 99	Hub gear made of cold rolled carbon steel (per ASTM A1008), molded into the plastic and pressed on pinion, with: - an outer diameter of 81,2 mm or more, but not more than 82,55 mm, - an inner diameter of 25,9 mm or more, but not more than 25,97 mm, - a height of the lower side of inner diameter of 11,63 mm or more, but not more than 12,13 mm, - a height of the upper side of inner diameter of 3,25 mm or more, but not more than 3,5 mm, - an overall height of 11,63 mm or more, but not more than 19,5 mm for use in the manufacture of vehicle's steering system (1)	ПОЛША	2545142	ново
8708 94 99	Shaft intermediate steering assembly as part of the steering column with: - a torsional stiffness of 25 Nm/degree or more, - a shaft assembly male tubular made of carbon steel welded tube (per GB/T 699 grade 20), - a shaft assembly female tubular made of carbon steel welded tube (per GB/T 699 grade 20),	ПОЛША	2550880	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- two spiders universal joint made of chromium alloy steel (per GB/T 5216 grade 20CrMnTiH), - a length in nominal telescope position of 396 mm or more but not more than 467 mm, - a coupling interface on both ends with internal toothing, - two cardan joints on both sides, - a telescope shaft function with a range of 74 mm or more but not more than 115 mm, for use in the manufacture of vehicle's steering system (1)			
8708 94 99	Lower assist shaft as part of the steering column made of carbon steel (per GB/T699 grade 45 or JIS G4051 grade S45C) with: - an ultimate torsional strength load of 325 Nm or more and J.A.E.L values of 275 Nm or more, - a length of 66,39 mm or more but not more than 88,64 mm, - an outer diameter of 27,47 mm or more but not more than 28,38 mm, - an inner hole of diameter 6,50 mm or more but not more than 6,58 mm, - an external 26-teeth spline with major diameter 21,18 mm or more but not more than 21,44 mm, - a knurling on a part of outer surface of major diameter 26,0 mm or more but not more than 26,1 mm, - with or without an external 24-tooth spline and with a major diameter 24,75 mm or more but not more than 25 mm, for use in the manufacture of vehicle's steering syste (1)	ПОЛША	2550954	ново
8708 94 99	Tubular steering shaft as part of the steering column made of carbon steel welded tube (per EN 10305/2, E235 + C or GB/T699 grade 20) with: - an ultimate torsional strength of 300 Nm or more and J.A.E.L values of 275 Nm or more, - a length of 245,48 mm or more but not more than 287,5 mm, - an outer diameter of 23,95 mm or more but not more than 32,25 mm, - an interface for steering wheel connection either in a form of an external 40-tooth spline with major diameter of 17,1 mm or more but not more than 17,5 mm and an internal thread	ПОЛША	2551185	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- M12x1,75-6H or in a form of an external hexagon with a short diagonal of 15,05 mm or more but not more than 15,35mm and an internal thread M10x1.5-6H, - an interface either in a form of an internal 10-tooth spline of length of 98 mm or more but not more than 160 mm, with minor diameter of 16,1 mm or more but not more than 16,4 or in a form of an internal 48-tooth spline of length of 151 mm or more but not more than 160 mm, with minor diameter of 23,2 mm or more but not more than 23,3 mm, for use in the manufacture of vehicle's steering system (1)			
8708 94 99	Lower shaft as part of the steering column made of aluminum alloy (per ASTM B221M grade 6105), air quenched and tempered with: - an ultimate torsional strength of 260 Nm or more, - a length of 296,7 mm or more but not more than 297,8 mm, - an external 18-tooth spline on all shaft length with major diameter of 28,7 mm or more but not - more than 29 mm, - an 18-tooth internal spline with a minor diameter of 19,7 mm or more but not more than 20 mm, for use in the manufacture of vehicle's steering system (1)	ПОЛША	2551124	ново
8708 94 99	Upper assist shaft as part of the steering column made of carbon steel (per GB/T699 grade 45) with: - an ultimate torsional strength load of 325 Nm or more and J.A.E.L values of 275 Nm or more, - a length of 165,3 mm or more but not more than 204,2 mm, - an outer diameter of 22,87 mm or more but not more than 22,92 mm, - an internal hole of diameter 6,50 or more but not more than 6,58 mm, - an external spline, for use in the manufacture of vehicle's steering system (1)	ПОЛША	2551037	ново
9503 00 75	Miniature engine: - consisting of a plastic body, - with shaft length 11 cm or more but not more than 15,5 cm,	ТУРЦИЯ	2558847	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- allowing the gears to rotate by means of the cables it contains transmitting electric current, for use in the manufacture of the toys under heading 9503 (1)			
9503 00 75	Miniature engine: - consisting of a metal body, - allowing the gears to rotate by means of the cables transmitting electric current, for use in the manufacture of the toys under heading 9503 (1)	ТУРЦИЯ	2558894	ново