МИНИСТЕРСТВО НА ФИНАНСИТЕ
АГЕНЦИЯ "МИТНИЦИ"
ЦЕНТРАЛНО МИТНИЧЕСКО УПРАВЛЕНИЕ

ИСКАНИЯ ЗА СУСПЕНДИРАНЕ НА МИТАТА ОТ 1 ЯНУАРИ 2026 г., ПОСТЪПИЛИ В ГЕНЕРАЛНА ДИРЕКЦИЯ "ДАНЪЧНО ОБЛАГАНЕ И МИТНИЧЕСКИ СЪЮЗ" НА ЕВРОПЕЙСКАТА КОМИСИЯ

1. Настоящият документ представя исканията за въвеждане на автономни мерки за суспендиране на митата на определени химически и индустриални стоки, постъпили в определения срок (15 март 2025 г.) в ГД "Данъчно облагане и митнически съюз" на Европейската комисия. Исканията се разглеждат в Работна група "Икономически тарифни въпроси" на ЕК и се предлагат за одобрение от Съвета на Европейския съюз. Мерките, които касаят, са за пълно или частично суспендиране на митата от 1 януари 2026 г.
2. Тарифните кодове и текстовите описания на стоките могат да претърпят допълнително уточняване. В настоящия документ са описани всички оригинални искания на държавите членки, както и на Република Турция в рамките на митническия съюз ЕС– Турция.
3. Исканията са подредени по възходящ ред съгласно Комбинираната номенклатура на ЕС.
4. Формулярът за възражение срещу искане от този списък се намира на адрес https://customs.bg/wps/portal/agency/home/info-business/customs-activities/suspending.
5. Български производители, които считат, че тези предложения накърняват икономическите им интереси могат да подадат възражения, като използват формуляр, чийто образец се намира на адрес https://customs.bg/wps/portal/agency/home/info-business/customs-activities/suspending. Срокът за подаване на възражения по нови искания е до 17.06.2025 г. (в Агенция"Митници" – 2.06.2025 г.), а по исканията за продължаване на мерките за суспендирания - до 09.05.2025 г.
6. Коментари по исканията могат да бъдат направени до 17.06.2025 г. за нови искания (в Агенция"Митници" – 2.06.2025 г.) и до 09.05.2025 г. за искания за продължаване на мерките. За целта се използва формулярът за подаване на възражения.

Възраженията и коментарите по исканията за суспендиране на митата, придружени с необходимите мотивационни документи се подават по факс: 02 / 9859 4066.

За допълнителна информация относно суспендирането на митата:
дирекция "Митническа дейност и методология"
02 / 9859 4452 – Бояна Господинова

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
2811 22 00	Silicon dioxide with a purity by weight of 98 % or more CAS RN 112926-00-8	РУМЪНИЯ	2410551	ново
2827 49 90	Zirconium dichloride oxide (CAS RN 7699-43-6) of a purity by weight of 95 % or more	АВСТРИЯ	2073341	ново
2903 29 00	trans-1,2-Dichloroethylene (CAS RN 156-60-5) with a purity by weight of 99 % or more	ФРАНЦИЯ	1710781	ново
2905 39 95	Propane-1,3-diol (CAS RN 504-63-2) with a purity by weight of 99 % or more	БЕЛГИЯ	2159167	ново
2905 39 95	2,5,7,10,11,14-hexaoxa-1,6-distibabicyclo[4.4.4]tetradecane (CAS RN 29736-75-2) with a purity by weight of 99 % or more	ИСПАНИЯ	2030799	ново
2906 29 00	(2-Bromo-5-iodophenyl)methanol (CAS RN 946525-30-0) with a purity by weight of 98 % or more	ИТАЛИЯ	1964394	ново
2912 49 00	5-(1,1-Dimethylethyl)-2-methoxybenzaldehyde (CAS RN 85943-26-6) with a purity by weight of 98 % or more	ИТАЛИЯ	1792518	ново
2914 50 00	7-hydroxy-3-4-dihydronaphthalen-1(2H)-one (CAS RN 22009-38-7) with a purity by weight of 98 % or more	ИТАЛИЯ	1939427	ново
2916 14 00	2-Hydroxyethyl methacrylate (CAS RN 868-77-9) with a purity by weight of 97 % or more	НИДЕРЛАНДИЯ	2278312	ново
2917 12 00	Bis(3,4-epoxycyclohexylmethyl)adipate (CAS RN 3130-19-6) of a purity by weight of 97 % or more	ГЕРМАНИЯ	2171718	ново
2917 19 80	Dibutyl itaconate (CAS RN 2155-60-4) with a purity of 96 % by weight or more	НИДЕРЛАНДИЯ	2168744	ново
2917 20 00	1,2,3,6-Tetrahydrophthalic anhydride (CAS RN 85-43-8) with a purity by weight of 98 % or more	НИДЕРЛАНДИЯ	2481545	ново
2918 29 00	3-hydroxy-2-naphthoic acid (CAS RN 92-70-6) with a purity by weight of 99 % or more	ИСПАНИЯ	1898599	ново
2918 30 00	2-(4-Chlorobenzoyl)benzoic acid (CAS RN 85-56-3) with a purity by weight of 99 % or more	НИДЕРЛАНДИЯ	2272516	ново
2918 30 00	Prohexadione-calcium (ISOM) (CAS RN 127277-53-6) with a purity by weight of 95 % or more	НИДЕРЛАНДИЯ	2204124	ново
2918 99 90	methyl-3-methoxyacrylate with a purity by weight of 98 % or more CAS RN 5788-17-0	ФИНЛАНДИЯ	2366645	ново
2918 99 90	3,4-Epoxycyclohexylmethyl-3',4'-epoxycyclohexane carboxylate (CAS RN 2386-87-0) of a purity by weight of 91 % or more	ГЕРМАНИЯ	2171914	ново
2920 29 00	Tris(2-chloroethyl) phosphite (CAS RN 140-08-9) with a purity by weight of 90 % or more	НИДЕРЛАНДИЯ	2312786	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
2922 29 00	4-Amino-2,3-dichlorophenol (CAS RN 39183-17-0) with a purity by weight by 98 % or more	ГЕРМАНИЯ	2065421	ново
2922 49 85	Magnesium;2-aminoacetate (CAS RN 14783-68-7) with a purity by weight of 100 %, imported in packages not less than 25Kg; not put up for retail sale	ИРЛАНДИЯ	2189820	ново
2923 10 00	Calcium Phosphoryl Choline Chloride (CAS RN 72556-74-2) with a purity by weight of 90 % or more	ИСПАНИЯ	2029862	ново
2924 29 70	Calcium bis[(2r,4s)-5-(biphenyl-4-yl)-4-(3-carboxypropionylamino)-2-methylpentanonic acid ethyl ester)] salt with a purity by weight of 98,0 % or more	СЛОВЕНИЯ ИРЛАНДИЯ	1902090	ново
2925 29 00	N-amidinosarcosine hydrate (CAS 6020-87-7) with a purity by weight of 99 % or more, imported in packages not less than 25 kg	ИРЛАНДИЯ	2166771	ново
2926 90 70	2,3,3,3-Tetrafluoro-2-(trifluoromethyl)propanenitrile (CAS RN 42532-60-5) with a purity by weight of 99 % or more	ФРАНЦИЯ	1713491	ново
2926 90 70	3,4-dimethoxybicyclo[4.2.0]octa-1,3,5,-triene-7-carbonitrile (CAS RN 35202-54-1) with a purity by weight of 97 % or more	ИСПАНИЯ	1790113	ново
2931 90 00	F3 – Catalyst of an organic hafnium compound in powder form (CAS RN 264926-41-2) or dissolved in hexane (CAS RN 657-27-2) with a purity of 95 % or more	АВСТРИЯ	2163644	ново
2931 90 00	Hydrogen tetrakis(pentafluorophenyl)borate(1-)—N,N-dimethylaniline (1:1) (CAS RN 118612-00-3) with a purity by weight of 99 % or more	АВСТРИЯ	2164499	ново
2932 20 90	6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide (CAS RN 1552-42-7) with a purity by weight of 96 % or more	НИДЕРЛАНДИЯ	2168134	ново
2933 39 99	(1R,2S,4R)-2-Benzhydrylquinuclidin-3-one (2R,3R)-2,3-dihydroxysuccinate (CAS RN 683206-54-4) with a purity by weight of 98 % or more	ИТАЛИЯ	1793363	ново
2933 99 80	(2R,3R)-2-(2,4-Difluorophenyl)-1-(1H-1,2,4-triazol-1-yl)butane-2,3-diol methanesulfonate (CAS RN 1175536-50-1) with a purity by weight of 98 % or more	ИТАЛИЯ	1793936	ново
2934 99 90	Disodium uridine-5'-monophosphate (CAS RN 3387-36-8) with a purity by weight of 98 % or more	ИСПАНИЯ	2028227	ново
2934 99 90	Nedosiran Sodium (CAS RN 2247026-22-6) with a purity by weight of 95 % or more	ДАНИЯ	2057866	ново
2934 99 90	[6R-[6α,7β(Z)]]-7-[2-furyl(methoxyimino)acetamido]-3-(hydroxymethyl)-8-oxo-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid (CAS RN 56271-94-4) with a purity by weight of 96 % or more	ИТАЛИЯ	1790941	ново
3808 99 90	Milbemycin oxime (CAS RN 129496-10-2), mixture of A3 (C31H43NO7) and A4 (C32H45NO7), predominantly A4, with a purity by weight of 95 % or more	ФРАНЦИЯ	1697141	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
3812 10 00	TBSI - Rubber vulcanizing agent consisting of a light white to light yellow-brown powder, the product is a preparation, with the following components: - N-(1,1-dimethylethyl) bis(2-benzothiazolesulfen) amide (CAS RN 3741-80-8) with a purity by weight of 98 % or more and White mineral oil (petroleum) (CAS RN 8042-47-5) with a purity by weight of 2 % or more	РУМЪНИЯ	2486402	ново
3824 99 92	Trimethylolpropane ethoxylate (CAS RN 50586-59-9)	НИДЕРЛАНДИЯ	2483059	ново
3824 99 92	Mixture of primary tert-alkylamines (CAS RN 68955-53-3)	ГЕРМАНИЯ	2279213	ново
3824 99 92	Pentanoic acid, 5-(dimethylamino)-2-methyl-5-oxo-,methyl ester (CAS RN 1174627-68-9) with a purity by weight of 75 % or more	ФРАНЦИЯ	1903259	ново
3824 99 96	Yttria Stabilized Zirconia (YSZ) (CAS RN 64417-98-7) of a purity by Zirconia of 90 % or more	АВСТРИЯ	2072871	ново
3901 10 10	Linear low-density polyethylene (ethylene-1-butene) (CAS RN 25087-34-7), - with a melt flow rate (MFR 190 °C/2.16 kg) of 0.43 or more but not more than 1.00 g/10 min, - with a density (ASTM D 1505) of 0.915 g/cm³ or more, but not more than 0.942 g/cm³.	ТУРЦИЯ	2246559	ново
3902 10 00	Polypropylene containing no plasticiser, - of a tensile strength: of 26 - 36 MPa (as determined by ISO 527 method), - of a melt Flow Rate (mfr) at 230 °C of 10 - 30 g/10 min (as determined by the ISO 1133 method), - of flexural modulus higher than 2300 MPa (as determined by the ISO 178 method), - with 60 % or more but not more 90 % by weight of Polypropylene, - with 10 % or more but not more than 45 % by weight of talc powder. recycled material is above 99 % Polypropylene component coming from a single source of polypropylene recycled.	ЧЕХИЯ	2277892	ново
3904 69 80	Polyvinylidene Difluoride (PVDF) (CAS RN 24937-79-9)	ТУРЦИЯ ФРАНЦИЯ	2275570	ново
3911 90 19	Benzenamine, 4,4'-oxybis-, polymer with 1,3-benzenediamime and 1,3-dihydro-1,3-dioxo-5-isobenzofurancarbonyl chloride (CAS RN 35463-82-2) or 5-Isobenzofurancarbonyl chloride, 1,3-dihydro-1,3-dioxo-, polymer with 4,4'-	БЕЛГИЯ	2225697	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	methylenebis[benzenamine] (CAS RN 25928-85-2) containing by weight not more than 35 % of additives			
3911 90 99	A mixture containing by weight: - 89 % or more but not more than 91 % of 1,4:5,8- Dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a- tetrahydro-4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and 9 % or more but not more than 11 % of Polypropylene Homopolymer (CAS RN 9003-07-0)	ИРЛАНДИЯ	2205779	ново
3920 62 19	Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers, badges and tapes, safety clothing and accessories thereof, or of school satchels, bags or similar containers	ИРЛАНДИЯ	2246820	ново
3921 19 00	Strip of microporous polytetrafluoroethylene on a support of a non-woven for use in the manufacture of filters for kidney dialysis equipment(1)	ИРЛАНДИЯ	2026850	ново
4016 99 57	Wiper rubber specifically designed for the manufacture of windshield wipers for motor vehicles under the tariff heading 8512 with; - a length of 300mm or more but not more than 700mm; made of with NRCR 60 Shore A structure	ТУРЦИЯ	2246416	ново
5402 33 00	Textured polyester yarn: - textured using single heater and double heater methods, - with a linear density of 83 dtex or more, but not more than 666 dtex, - with an average minimum tenacity of 32 cN/tex, - with a filament count of 36 or more, but not more than 192, - with an elongation of 16 % or more, but not more than 33 %, - with a boiling water shrinkage of 3 % or more, but not more than 8 %, with a content of preparation 1 % or more, but not more than 3 %	ПОЛША	2204850	ново
5403 31 00	Viscose rayon filament yarn centrifugal, measuring 80 decitex or more, but not more than 88 decitex, consisting of a number of monofilaments of 24 or more, but not more than 36.	ИСПАНИЯ	1835626	ново
5602 10 19	Needle punched felt with a polyvinyl alcohol content of 20 % or more but not more than 40 %	ТУРЦИЯ	2281825	ново
5902 10 10	Cord fabric obtained by impregnating nylon or other polyamides with rubber containing by weight of:	ТУРЦИЯ	2235613	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- 90 % or more but not more than 98 % Polyamide 6 - 2 % or more but not more than 7 % RFL (Resorcinol Formaldehyde Latex) and - 1 % or less cotton yarn for use in any type of transport vehicle tire			
7019 80 10	Vacuum Insulation Panel consisting of a hermetic casing made of multi-layer foil with aluminum surrounding a rigid core, devoid of air, used for thermal insulation of the interior of the fridge-freezer: - the main insulating material of the product is fiberglass (wool fiber) (min 70 %), - panel thickness 15 mm or more, but not more than 35 mm, - width 165 mm or more, but not more than 510 mm, - length 375 mm or more, but not more than 1875 mm, - thermal conductivity coefficient K-factor below 0.0015 kcal/(h·m·°C), ambient temperature during operation from -50 °C or more, but not more than 80°C	ПОЛША	2165498	ново
8109 29 00	Non-alloy zirconium sponges or ingots containing by weight more than 0,01 % of hafnium for use in the manufacture of tubes, bars or ingots enlarged by remelting for the non-nuclear industry (1)	ШВЕЦИЯ	1835222	ново
8207 19 10	Inserts for drilling tools with working parts of agglomerated diamonds	ТУРЦИЯ	2246032	ново
8409 91 00	Connecting rod for connecting pistons to the crankshaft of a passenger car engine: - made of an alloy containing 96 % steel and the remainder being titanium, vanadium, aluminum, chromium, nickel, copper, phosphorus, silicon, sulfur, manganese, - with two connecting rod bolts, - with plain bearing, - of a length of 120 mm or more but not more than 160 mm, - with a surface roughness corresponding to ISO 4287-1997, for use in the manufacture of motor vehicle engines (1)	ПОЛША	2947092	ново
8414 30 20	Hermetic compressor for R600a refrigerant for the production of refrigerators and fridge-freezers:	ПОЛША	2446092	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- with a power not exceeding 0.4 KW, - pre-filled with mineral lubricant oil from 110 cm3 to 175 cm3, - suction and processing pipe inner diameter from 6.34 to 6.74 mm, thickness from 0.6 to 0.8 mm, - discharge pipe inner diameter from 4.9 to 5.1 mm, thickness from 0.75 to 0.95 mm, - hermetic clamp and bracket, which can be assembled with a plastic cover, - speed range from 900 rpm to 4500 rpm, - driven by a brushless DC electric motor, - cooling capacity from 76 to 110 W at 1800 rpm (1)			
8414 59 25	DC Brushless Axial Fan, to be used in instrument clusters, speedometers, multimedia and infotainment systems for transport vehicles, with: - a rated voltage between: 3 to 16 VDC - an operating voltage between: 3 to 16 VDC - an rated current between: 0,03 to 0,30 A - an input power between: 0,3 to 1,5 W - a rotation speed between: 2500 to 10000 R.P.M. - an air flow of not more than 25 CFM (cubic foot per minute) - an air pressure of not more than 10 mmH2O - an overall sound of not more than 45 dB(A) - a diameter of not more than 65mm With or without an heat sink incorporated	ПОРТУГАЛИЯ	3032672	ново
8414 90 00	Air conditioning compressor housing component made of aluminum alloy for installation in electric air conditioning compressors for motor vehicles: - with a width of 100 mm or more but not more than 220 mm, - with a length of 100 mm or more but not more than 230 mm, - with a height of 80 mm or more but not more than 180 mm, - with one single central bore, - machined or unwrought,	УНГАРИЯ	2464396	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- whether or not impregnated, with one suction port or without.			
8418 99 90	Evaporator, which is a type of heat exchanger used in refrigerators and refrigerators with freezers: - with an external dimensions from 362x244x60mm to 398.4x503x60 mm, - with aluminium radiators with dimensions from 60x26.7 mm to 60.2x27.3 mm, - with an aluminium tube with an external diameter of 8.4 - 8.5 mm, - with a straight internal channel or with an elongated internal channel with grooves of 40 pcs grooves, - with 229 to 307 radiating fins, - without heaters or max. with two heaters with power of 40 W or more, but not more than 140 W, without thermal fuses or with two such fuses with a melting point of 77 °C	ПОЛША	2705253	ново
8418 99 90	Condenser for a refrigerator, which is a heat exchanger, mounted on the back of refrigerators and fridge-freezers: - a steel pipe with a dimeter of 4.68-4.81 mm, a wall thickness of 0.52-0.65 mm, - 26-30 pcs of horizontal pipe sections, each straight with a length of 450-455 mm, spaced every 40 mm between each horizontal part, - having from 112 to 174 pcs welded steel rods with a diameter of 1.3 mm and a length of 1002-1322 mm, - having 3 clips, - having 4 brackets welded between the rods, - having an optional decorative cover made of black polyvinyl chloride, a length of 443 mm or more, but not more than 450 mm	ПОЛША	2727561	ново
8481 80 99	Service valve which suits for R410A or R32 gas while connecting indoor and outdoor units with: - a withstanding pressure of the valve body of 6,3 MPa, - a leakage ratio of less than 1.6 g/a, - an impurity ratio of less than 1.2 mg/PCS,	ТУРЦИЯ	2400121	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- an airtight pressure of the valve body of 4.2 Mpa for use in the manufacture of air conditioners (1)			
8483 50 80	Flywheel for damping torsional vibrations and oscillations within the car's drivetrain: - with a total moment of inertia of 0.082 kg.m², - with a weight of 7 kg or more, but not more than 8 kg, - with a diameter of 250 mm or more, but not more than 280 mm for use in the manufacture of motor vehicles (1)	СЛОВАКИЯ	2947464	ново
8501 31 00	DC motor, brushless, integrated with an Electronic Control Unit (ECU), defined as a Power Pack with: - a safety feature and mechanism designed for prevention of critical hazards like self-steer by single failure, - a CAN-communication interface, - an external sensor interface, - operating temperature range of -40°C to 95°C or broader, - compliance with standard IP6K9K for water and dustproofness, - supply voltage of 9 V or more, but not more than 16 V, - rated power output of 500 W or more, but not higher than 750 W, - rated torque of 3 Nm or more, but not more than 6 Nm, - length of 150 mm or more, but not more than 250 mm, - width of 100 mm or more, but not more than 150 mm, height of 80 mm or more, but not more than 120 mm	ПОЛША	2701255	ново
8501 31 00	Brushless DC electric motor: - with an output power of 200 W or greater, but not exceeding 700 W, - with a supply voltage of 30 V or greater, but not exceeding 60 V, - with a torque of 30 Nm or greater, but not exceeding 200 Nm, - with an outer diameter of 135 mm or greater but not exceeding 175 mm, - with a weight of 2 kg or greater but not exceeding 5 kg, - designed to be mounted in a frame, front or rear bicycle wheel, equipped with an LCD display	ПОЛША	2705655	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
8501 40 20	Single-phase brushless AC motor with an output not exceeding 750W, incomplete, for drum drive of washing machines and washer-dryers, consisting of rotor and stator: - rotor on the inside is equipped with a ring of 12 magnets housed in a steel casing, - stator with an internal diameter of 206.6 mm (± 0.5), external diameter of 265.0 mm (± 0.2) and width of 37.2 mm to 47.8 mm, - with a rated power not exceeding 750 W, - with a mass of 5 kg or more, used in the production of washing machines, washer-dryers equipped with a drum with direct drive	ПОЛША	2946361	ново
8507 60 00	Rechargeable lithium-ion batteries: - with fuse, - with a battery cell design, - using LFP technology, - with a length of 1055 mm or more, but not more than 1065 mm, - with a width of 630 mm or more, but not more than 640 mm, - of a height of 242 mm or more but not more than 253 mm, - of a mass of 262 kg or more but not more than 270 kg, - with a capacity of 268 Ah, - with upper outer casing made of composite material, - with IP68 protection level or more, - with energy density of 264 Wh/dm3 or higer, - with specific energy of 167 Wh/kg or higer, - without contactors, for use in the manufacture of batteries for electric buses (1)	ПОЛША	2730921	ново
8507 60 00	Lithium-ion rechargeable batteries with: - a length of 700 mm or more, but not more than 2 820 mm, - a width of 935 mm or more, but not more than 1 660 mm, - a height of 85 mm or more, but not more than 700 mm, - a weight of 250 kg or more, but not more than 700 kg,	ИСПАНИЯ	2479524	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- a power of not more than 175 kWh a nominal voltage of 650V or more, but not more than 800V			
8507 60 00	Lithium Iron Phosphate (LFP) Blade Cell (in-line anode and cathode position to both ends of cell) with embedded anti-vibration bracket: - with a length of 110 mm or more but not more than 145.5 mm, - with a width of 40 mm or more but not more than 58.2 mm, - with a height of 401 mm or more but not more than 405.2 mm, - with a weight of 3500 gr (± %0,5) or more but not more than 7000 gr (± %0,5), with a nominal Capacity of 150 Ah or more but not more than 300 Ah	ТУРЦИЯ	2944920	ново
8507 60 00	A rechargeable lithium-ion battery pack, based on lithium nickel manganese cobalt technology (NCM) with: - a length of 2584 mm or more, but not exceeding 2856 mm, - a width of 1028 mm or more, but not exceeding 1132 mm, - a height of 160 mm or more, but not exceeding 181 mm, - a weight of 600 kg or more, but not exceeding 651 kg, - a power not exceeding of 115 kWh or more, but not exceeding 128 kWh, - a nominal capacity of 148 Ah or more, but not exceeding 174 Ah, a nominal voltage of 718 V or more, but not exceeding 793 V.	БЕЛГИЯ	2478190	ново
8507 60 00	A rechargeable lithium-ion battery, containing a fuse, in cell-to-pack design, with: - a length of 1 050 mm or more, but not more than 1 070 mm, - a width of 624 mm or more, but not more than 636 mm, - a height of 235 mm or more, but not more than 245 mm, - a mass of 214,4 kg or more, but not more than 227,6 kg, - a capacity of 228 Ah, - using LFP technology, - an upper outer casing of the battery made of a composite material, - battery with R100.02 certificate, - protection class IP 68 (battery connected to the system), - without contactors, - with volumetric energy of 220Wh/l or higer,	ПОЛША	2704328	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- gravimetric energy of 159Wh/kg or higer, for use in the the manufacture of batteries for electric buses (1)			
8507 60 00	Rechargeable lithium-ion batteries: - with fuse, - with a battery cell design, - using LFP technology, - with a length of 1345 mm or more, but not more than 1355 mm, - with a width of 655 mm or more, but not more than 665 mm, - with a height of 238 mm or more, but not more than 248 mm, - with a mass of 272 kg or more, but not more than 275 kg, - with a capacity of 95 Ah, - with upper outer casing made of composite material, - with IP68 protection level, or more, - with energy density of 135 Wh/dm3 or higer, - with specific energy of 112 Wh/kg or higer, - without contactors, for use in the manufacture of batteries for electric buses (1)	ПОЛША	2733173	ново
8507 60 00	A rechargeable lithium-ion battery pack, based on Lithium-iron-phosphate technology (LFP) with: - a length of 2613 mm or more, but not exceeding 2888 mm, - a width of 1026 mm or more, but not exceeding 1134 mm, - a height of 257 mm or more, but not exceeding 284 mm, - a weight of 1089 kg or more, but not exceeding 1203 kg, - a power of 170 or more, but not exceeding 182 kWh, - a nominal capacity of 215 or more, but not exceeding 245 Ah, a nominal voltage of 729 or more, but not exceeding 805 V	БЕЛГИЯ	2478851	ново
8507 60 00	Cells for the manufacture of lithium-ion electric accumulators with: - a length of 250 mm or more, but not more than 265 mm, - -a width of 22 mm or more, but not more than 26 mm, - -a height of 100 mm or more, but not more than 110 mm, - -a weight of 1,4 kg or more, but not more than 1,6 kg,	ЧЕХИЯ	2477462	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	-a capacity of not more than 92 Ah and a nominal energy of less than 291 Wh			
8512 20 00	Sub-assembly reflectors and components for car rear lights: - containing two or three PCBA with a connection socket and LED, - with central control module (CCE) connected through wired harness, - with a main reflector, a sub-reflector and inner lens scattering the light made of plastic, - with depth of 119 mm or more, but not more than 146 mm, - with width of 142 mm or more, but not more than 490 mm, - with a height of 93 mm or more, but not more than 100 mm, - a weight of 414 g or more, but not more than 578 g, with lightguide	ПОЛША	2443446	ново
8537 10 91	Control unit for the automatic transmission oil pump for efficient cooling and oil pressure regulation in the car's drivetrain: - liquid-cooled, - with an operating voltage of 9 V DC or more, but not more than 16 V, - with a height of 165 mm or more, but not more than 190 mm, - with a width of 40 mm, but not more than 60 mm, - with a length of 170 mm or more, but not more than 195 mm, - in a casing, - with one or more connectors, and for use in the manufacture of hybrid motor vehicles (1)	СЛОВАКИЯ	2947957	ново
8549 13 20	- Spent lithium-ion or nickel metal hydride electric accumulators	БЕЛГИЯ	2695775	ново
8708 50 99	Roll rod assembly for the front suspension in vehicles for connecting the stabilizer to the suspension components: - made of aluminum, rubber, and plastic, - with a height of 270 mm or more, but not more than 300 mm, - with a width of 50 mm, but not more than 65 mm, - with a length of 150 mm or more, but not more than 170 mm, for use in the manufacture of motor vehicles (1)	СЛОВАКИЯ	2948134	ново
8708 95 99	The airbag assembly for enhancing safety in the event of a car collision: - with a wiring harness,	СЛОВАКИЯ	2948356	ново

ТАРИФЕН КОД	ОПИСАНИЕ НА СТОКАТА	ДЪРЖАВА, ПОДАЛА ИСКАНЕТО	TAXUD	ВИД НА ИСКАНЕТО
	- with a polyamide inflatable safety cushion, - with an inflator containing cold gas, - in a housing, - with mounting brackets for use in the manufacture of motor vehicles(1)			
8708 99 97	Mounting bracket of front radiator or intercooler whether or not with rubber cushioning for use in the manufacture of goods of Chapter 87 (1)	СЛОВАКИЯ	2696943	ново
8714 93 00	Gear set without a pawl mechanism, mounted on a hub drum, connecting sprockets: - with 7 row or more sprockets, but not more than 12 row sprockets, - with 10 teeth per gear or more, but not more than 52 teeth, - with a weight of 200 g or greater, but not exceeding 800 g, - with sprockets made of nickel-plated steel or aluminium for use in the manufacture of bicycles and e-bikes (1)	ПОЛША	2411868	ново
9401 99 20	Cassette, a locking mechanism mounted on the seat skeleton, designed for use in the manufacture of passenger car seats	ТУРЦИЯ	3080179	ново